

INTERNATIONAL STANDARD



**Multicore and symmetrical pair/quad cables for digital communications –
Part 7: Symmetrical pair cables with transmission characteristics up to
1 200 MHz – Sectional specification for digital and analogue communication
cables**



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2023 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 300 terminological entries in English and French, with equivalent terms in 19 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IECNORM.COM : Click to view the full PDF of IEC 6187-7:2023 RVV

INTERNATIONAL STANDARD



**Multicore and symmetrical pair/quad cables for digital communications –
Part 7: Symmetrical pair cables with transmission characteristics up to
1 200 MHz – Sectional specification for digital and analogue communication
cables**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 33.120.20

ISBN 978-2-8322-6487-4

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	5
1 General	8
1 Scope	8
2 Normative references	8
3 Terms and definitions	9
4 Installation consideration	9
4.1 General remarks	9
4.2 Bending radius of installed cable.....	9
4.3 Climatic conditions.....	9
5 Material and cable construction	9
5.1 General remarks	9
5.2 Cable construction	10
5.2.1 General	10
5.2.2 Conductor.....	10
5.2.3 Insulation.....	10
5.2.4 Cable element	10
5.2.5 Cable make-up	10
5.2.6 Screening of the cable core	11
5.2.7 Sheath.....	11
5.2.8 Identification.....	11
5.2.9 Finished cable	11
6 Characteristics and requirements	12
6.1 General remarks	12
6.2 Electrical characteristics and tests	12
6.2.1 Conductor resistance.....	12
6.2.2 Resistance unbalance within a pair.....	12
6.2.3 Dielectric strength.....	12
6.2.4 Insulation resistance.....	12
6.2.5 Mutual capacitance.....	12
6.2.6 Capacitance unbalance pair to ground	12
6.2.7 Transfer impedance.....	12
6.2.8 Coupling attenuation.....	13
6.2.9 Current-carrying capacity.....	13
6.2.10 Resistance of the screen	13
6.3 Transmission characteristics	13
6.3.1 General remark.....	13
6.3.2 Velocity of propagation (phase velocity).....	14
6.3.3 Phase delay and differential phase delay (delay skew)	14
6.3.4 Attenuation (α).....	14
6.3.5 Unbalance attenuation near-end (<i>TCL</i> , <i>EL TCL</i>).....	15
6.3.6 Near-end crosstalk (NEXT) (<i>PS NEXT</i> , <i>NEXT</i>)	16
6.3.7 Far-end crosstalk (FEXT) (<i>PS ACR-F</i> , <i>ACR-F</i>)	17
6.3.8 Alien (exogenous) near-end crosstalk	17
6.3.9 Alien (exogenous) far-end crosstalk.....	18
6.3.10 Alien (exogenous) crosstalk of bundled cables	18
6.3.11 Characteristic Impedance	18

6.3.12	Return loss (<i>RL</i>).....	17
3.3.8	Screening attenuation	19
6.4	Mechanical and dimensional characteristics and requirements.....	19
6.4.1	Dimensional requirements	19
6.4.2	Elongation at break of the conductors.....	19
6.4.3	Tensile strength of the insulation	19
6.4.4	Elongation at break of the insulation	19
6.4.5	Adhesion of the insulation to the conductor.....	19
6.4.6	Elongation at break of the sheath	19
6.4.7	Tensile strength of the sheath.....	19
6.4.8	Crush test of the cable.....	19
6.4.9	Impact test of the cable	19
6.4.10	Bending under tension.....	19
6.4.11	Repeated bending of the cable	20
6.4.12	Tensile performance of the cable	20
6.4.13	Shock-test requirements of the cable	20
6.4.14	Bump-test requirements of the cable	20
6.4.15	Vibration-test requirements of the cable.....	20
6.5	Environmental characteristics	20
6.5.1	Shrinkage of insulation	20
6.5.2	Wrapping test of insulation after thermal ageing	20
6.5.3	Bending test of insulation at low temperature.....	20
6.5.4	Elongation at break of the sheath after ageing	20
6.5.5	Tensile strength of the sheath after ageing	20
6.5.6	Sheath pressure at high temperature	20
6.5.7	Cold bend test of the cable.....	21
6.5.8	Heat Hot shock test	21
6.5.9	Damp heat steady state	21
6.5.10	Solar radiation (UV)	21
6.5.11	Solvents and contaminating fluids.....	21
6.5.12	Salt mist and sulphur dioxide	21
6.5.13	Water immersion	21
6.5.14	Hygroscopicity	21
6.5.15	Wicking.....	21
6.5.16	Flame propagation characteristics of a single cable	21
6.5.17	Flame propagation characteristics of bunched cables	21
3.5.11	Acid gas evolution	21
6.5.18	Resistance to fire.....	21
6.5.19	Halogen gas evolution	22
6.5.20	Smoke generation.....	22
6.5.21	Toxic gas emission	22
3.5.14	Combined flame and smoke test	22
6.5.22	Integrated fire test	22
7	Introduction to the blank detail specification	21
Annex A (informative)	Blank detail specification	23
Bibliography		28
Table 1 – Transfer impedance		13

Table 2 – Coupling attenuation	13
Table 3 – Attenuation, constant values	15
Table 4 – Attenuation values.....	15
Table 5 – Near-end crosstalk, power-sum (<i>PS NEXT</i>).....	16
Table 6 – Far-end crosstalk (FEXT) (<i>PS ACR-F</i>)	17
Table 7 – Return loss.....	18

IECNORM.COM : Click to view the full PDF of IEC 61156-7:2023 RLV

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**MULTICORE AND SYMMETRICAL PAIR/QUAD CABLES
FOR DIGITAL COMMUNICATIONS –****Part 7: Symmetrical pair cables with transmission
characteristics up to 1 200 MHz –
Sectional specification for digital and analogue
communication cables**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This redline version of the official IEC Standard allows the user to identify the changes made to the previous edition IEC 61156-7:2003+AMD1:2012 CSV. A vertical bar appears in the margin wherever a change has been made. Additions are in green text, deletions are in strikethrough red text.

IEC 61156-7 has been prepared by subcommittee 46C: Wires and symmetrical cables, of IEC technical committee 46: Cables, wires, waveguides, RF connectors, RF and microwave passive components and accessories. It is an International Standard.

This part of IEC 61156 is to be read in conjunction with IEC 61156-1:2023.

This second edition cancels and replaces the first edition published in 2003 and Amendment 1:2012. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) restructure all text to comply with ISO/IEC Directives Part 2;
- b) align clauses with IEC 61156-1:2023;
- c) remove the clause related to screening attenuation as it is no longer a test to be performed (replaced by coupling attenuation);
- d) replace the IEC 62153-4-2 method (injection clamp) with IEC 61156-4-5 (absorbing clamp) for coupling attenuation measurement to be consistent with all other parts of the IEC 61156 series;
- e) include IEC 62153-4-9 test method (triaxial) for coupling attenuation measurement to be consistent with all other parts of the IEC 61156 series;
- f) incorporate the blank detail specification.

The text of this International Standard is based on the following documents:

Draft	Report on voting
46C/1228/CDV	46C/1233/RVC

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

A list of all parts in the IEC 61156 series, published under the general title *Multicore and symmetrical pair/quad cables for digital communications*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

IECNORM.COM : Click to view the full PDF of IEC 61156-7:2023 RLV

MULTICORE AND SYMMETRICAL PAIR/QUAD CABLES FOR DIGITAL COMMUNICATIONS –

Part 7: Symmetrical pair cables with transmission characteristics up to 1 200 MHz – Sectional specification for digital and analogue communication cables

~~1~~ General

1 Scope

This part of IEC 61156 specifies cables that ~~may~~ can be used for various communication systems as well as for analogue systems, such as video, that exist or are under development and which may use as many as four pairs simultaneously. In this sense, this sectional specification provides the cable characteristics required by system developers to evaluate new systems as well as to enhance present systems.

It covers a cable having four individually screened (~~STPS~~/FTP) pairs. The cable ~~may~~ can be provided with a common screen over the cable core.

The transmission characteristics are specified up to a frequency of 1 200 MHz and at a temperature of 20 °C.

The cables covered by this sectional specification are intended to operate with voltages and currents normally encountered in communication systems and support the delivery of DC low voltage remote powering applications. These cables are not intended to be used in conjunction with low impedance sources, for example the electric power supply of public utility mains.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

~~IEC 60189-1:1986, Low-frequency cables and wires with PVC insulation and PVC sheath – Part 1: General test and measuring methods~~

IEC 60304, Standard colours for insulation for low-frequency cables and wires

IEC 61156-1:2002, Multicore and symmetrical pair/quad cables for digital communications – Part 1: Generic specification

~~IEC 61156-7-1, Multicore and symmetrical pair/quad cables for digital communications – Part 7-1: Symmetrical pair cables with transmission characteristics up to 1 200 MHz – Blank detail specification for digital and analog communication cables~~

~~IEC 62153-4-2, Metallic telecommunication cable test methods – Part 4-2: Electromagnetic compatibility (EMC) – Screening and coupling attenuation – Injection clamp method~~

IEC 62153-4-3, *Metallic communication cable test methods – Part 4-3: Electromagnetic compatibility (EMC) – Surface transfer impedance – Triaxial method*

IEC 62153-4-5, *Metallic communication cable test methods – Part 4-5: Electromagnetic compatibility (EMC) – Screening or coupling attenuation – Absorbing clamp method*

IEC 62153-4-9, *Metallic communication cable test methods – Part 4-9: Electromagnetic compatibility (EMC) – Coupling attenuation of screened balanced cables, triaxial method*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 61156-1 apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- IEC Electropedia: available at <https://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

4 Installation consideration

~~Under consideration.~~

4.1 General remarks

Installation considerations are defined in IEC 61156-1.

4.2 Bending radius of installed cable

The bending radius of the installed cable shall not be less than 4 times the outside diameter of the cable.

4.3 Climatic conditions

Under static conditions, the cables shall operate in the temperature range from –20 °C to +60 °C. The temperature dependence of the cables is specified for screened cables and should be taken into account for the design of actual cabling systems.

The recommended temperature range during installation should be indicated in the relevant detail specification.

When applications demand remote powering, the maximum temperature of the conductor shall not exceed the maximum operating temperature of the cable. Dielectric performance can be changed permanently due to over exposure of high temperatures.

5 Material and cable construction

5.1 General remarks

The choice of materials and cable construction shall be suitable for the intended application and installation of the cable. Particular care ~~shall~~ **should** be taken to meet any special requirements for fire performance (such as burning properties, smoke generation, evolution of halogen gas, etc.) and remote powering. ~~A detail specification may be prepared.~~

5.2 Cable construction

5.2.1 General

The cable construction shall be in accordance with the materials, dimensions and assembly details given in the relevant detail specification.

5.2.2 Conductor

The conductor shall be a solid annealed copper conductor, in accordance with IEC 61156-1, and ~~shall~~ should have a nominal diameter between 0,5 mm and ~~0,8 mm~~ 0,65 mm.

A conductor diameter of up to 0,8 mm may be used.

5.2.3 Insulation

5.2.3.1 Insulation material

The conductor shall be insulated with a suitable thermoplastic material. Examples of suitable materials are:

- polyolefin;
- fluoropolymer;
- low-smoke ~~zero~~-halogen-free thermoplastic material.

The insulation may be solid or cellular with or without a solid dielectric skin. The insulation shall be continuous and shall have a thickness such that the completed cable meets the specified requirements. The nominal thickness of the insulation shall be compatible with the method of conductor termination.

5.2.3.2 Colour code of insulation

The colour code is not specified but shall be indicated in the relevant detail specification. The colours shall be readily identifiable and shall correspond reasonably with the standard colours shown in IEC 60304.

NOTE It is acceptable to mark or stripe the "a" wire with the colour of the "b" wire to facilitate pair identification.

5.2.4 Cable element

5.2.4.1 Cable element type

The cable element shall be a ~~tested~~ screened twisted pair.

5.2.4.2 Screening of the cable element

The screen for the cable element shall be in accordance with IEC 61156-1. If a braid is used, the minimum braid coverage shall be such as to meet the screening requirements of this document. The individual components used to screen the cable element shall be in electrical contact.

5.2.5 Cable make-up

The cable elements shall be assembled to form the cable core.

The core of the cable may be ~~protected by wrappings of a non-hygroscopic tape~~ wrapped with a protective layer of non-hygroscopic and non-wicking material.

5.2.6 Screening of the cable core

A screen for the cable core may be provided. The screen shall be in accordance with IEC 61156-1.

5.2.7 Sheath

The sheath material shall consist of a suitable thermoplastic material.

Examples of suitable materials are:

- polyolefin;
- PVC;
- fluoropolymer;
- low-smoke ~~zero~~-halogen-free thermoplastic material.

The sheath shall be continuous, having a ~~uniform~~ thickness as uniform as possible. A non-metallic ripcord may be provided. When provided, the ripcord shall be non-hygroscopic and non-wicking.

~~2.2.11 Colour of sheath~~

The colour of the sheath is not specified but should be ~~stated~~ specified in the relevant detail specification.

5.2.8 Identification

5.2.8.1 Cable marking

Each length of cable shall ~~be identified as to~~ bear the ~~manufacturer~~ name of the supplier and the cable type and, when ~~indicated in the relevant detail specification~~ provided, the year of manufacture, using one of the following methods:

- a) ~~appropriately~~ coloured threads or tapes;
- b) ~~with a~~ printed tape;
- c) printing on the cable core wrapping;
- d) marking on the sheath.

Additional markings, such as length marking, etc., are permitted ~~on the cable sheath. When~~. If used, such markings should be indicated in the relevant detail specification.

5.2.8.2 Labelling

The following information shall be provided either on a label attached to each length of finished cable or on the outside of the product package:

- a) type of cable;
- b) supplier's name or logo;
- c) year of manufacture;
- d) length of cable in metres.

5.2.9 Finished cable

The finished cable shall be adequately protected for storage and shipment.

6 Characteristics and requirements

6.1 General remarks

Clause 6 lists the characteristics and minimum requirements of a cable complying with this document. Test methods shall be in accordance with IEC 61156-1. ~~A detail specification may be prepared to identify a specific product and its performance capabilities (see Clause 4).~~

6.2 Electrical characteristics and tests

~~The tests shall be carried out on a cable length of not less than 100 m unless otherwise specified.~~

6.2.1 Conductor resistance

~~When measured in accordance with 5.1 of IEC 60189-1,~~ The maximum ~~loop~~ conductor resistance shall not exceed ~~17,0~~ 8,5 $\Omega/100$ m of cable.

6.2.2 Resistance unbalance within a pair

~~When measured in accordance with 2.1.1 of IEC 61156-1,~~ The resistance unbalance ~~of~~ within a pair shall not exceed 2,0 %.

6.2.3 Dielectric strength

The test shall be performed on conductor/conductor and conductor/screen with 1,0 kV DC for 1 min or, alternately, with 2,5 kV DC for 2 s.

An AC voltage may be used. The AC voltage levels in these cases shall be 0,7 kV AC for 1 min or, alternately, 1,7 kV AC for 2 s.

NOTE When installed in conjunction with power cables, local regulations may require a higher test voltage.

6.2.4 Insulation resistance

The test, immediately after the dielectric strength test, shall be performed ~~both~~ on:

- conductor/conductor;
- conductor/screen.

The minimum insulation resistance at 20 °C shall not be less than 5 000 M Ω ·km.

6.2.5 Mutual capacitance

The mutual capacitance is not specified but may be indicated in the relevant detail specification.

6.2.6 Capacitance unbalance pair to ground

The maximum capacitance unbalance pair to ground shall not exceed 1 200 pF/km at a frequency of 1 kHz.

6.2.7 Transfer impedance

When measured using the triaxial method (IEC 62153-4-3), the transfer impedance shall not exceed the values listed in Table 1 at the indicated frequencies.

Table 1 – Transfer impedance

Frequency MHz	Max. surface transfer impedance mΩ/m
1	10
10	10
30	30
100	60

Frequency range MHz	Maximum surface transfer impedance mΩ/m
1 to 10	10
10 to 100	$10 \times f/10$
NOTE Values in the range 10 MHz to 100 MHz are equal to IEC 61156-5, Grade 1.	

6.2.8 Coupling attenuation

When measured ~~according to IEC 62153-4-2, the coupling attenuation shall be equal to, or greater than, the values~~ using the absorbing clamp method (IEC 62153-4-5) or the triaxial method (IEC 62153-4-9), the coupling attenuation in the frequency range from 30 MHz to 1 200 MHz shall meet the requirements indicated in Table 2.

Table 2 – Coupling attenuation

Frequency range MHz	Minimum coupling attenuation dB
30 to 100	85,0
100 to 1 200	$85,0 - 20 \times \log_{10}(f/100)$

NOTE Values in the range 30 MHz to 1 000 MHz are equal to IEC 61156-5, Type I.

6.2.9 Current-carrying capacity

The maximum current-carrying capacity is not specified but may be indicated in the relevant detail specification. Further guidance with respect to current carrying capacity is provided by ISO/IEC TS 29125 and the test method described in IEC 61156-1-4.

6.2.10 Resistance of the screen

The maximum longitudinal DC resistance value of the individual screens or an overall screen shall be less than 15 mΩ/m.

6.3 Transmission characteristics

6.3.1 General remark

All the tests shall be carried out on a cable length of 100 m, unless otherwise specified.

~~3.3.1 Velocity of propagation, delay and differential delay (delay skew)~~

6.3.2 Velocity of propagation (phase velocity)

The minimum velocity of propagation for any screened cable element shall be equal to, or greater than, $0,6 \times c$ (c is the speed of light in vacuum) for all frequencies between 4 MHz and 1 200 MHz.

NOTE The velocity of propagation, group velocity and phase velocity are approximately equal for frequencies greater than 4 MHz when measured on symmetric cables, i.e. when the cables are operated in a balanced mode.

6.3.3 Phase delay and differential phase delay (delay skew)

6.3.3.1 Phase delay

~~The delay for a specified length of cable is understood as the inverse of the velocity of propagation. The maximum delay shall be less than or equal to:~~

~~$$\text{delay} = 500 + \frac{36}{\sqrt{f}} \quad [\text{ns}/100 \text{ m}] \quad (1)$$~~

The phase delay, τ , shall not exceed the value obtained from:

$$\tau = 500 + \frac{36}{\sqrt{f}} \quad [\text{ns} / 100 \text{ m}] \quad (1)$$

where

τ is the phase delay in ns/100 m;

f is the frequency in MHz.

6.3.3.2 Differential phase delay (delay skew)

Differential phase delay (delay skew) is the difference in phase delay between any two screened cable elements.

When the phase delay is measured at $-20 \text{ }^{\circ}\text{C} \pm 2 \text{ }^{\circ}\text{C}$, $20 \text{ }^{\circ}\text{C} \pm 3 \text{ }^{\circ}\text{C}$ and $60 \text{ }^{\circ}\text{C} \pm 1 \text{ }^{\circ}\text{C}$, the maximum differential phase delay (delay skew) at a given temperature shall not be greater than 25,0 ns/100 m in the frequency range from 4 MHz to 1 200 MHz.

6.3.3.3 Environmental effects

The differential delay (delay skew) due to temperature shall not vary by more than ± 10 ns/100 m over the temperature range from $-20 \text{ }^{\circ}\text{C}$ to $+60 \text{ }^{\circ}\text{C}$ while still meeting the differential phase delay (delay skew) of 6.3.3.2.

6.3.4 Attenuation (α)

6.3.4.1 Attenuation at 20 °C operating temperature

The maximum attenuation α of any pair in the frequency range 4 MHz to 1 200 MHz shall be less than, or equal to, the value obtained from Formula (2) using the corresponding values of the constants given in Table 3.

$$\alpha = A \times \sqrt{f} + B \times f + \frac{C}{\sqrt{f}} \quad [\text{dB} / 100 \text{ m}] \quad (2)$$

Table 3 – Attenuation, constant values

Constants		
A	B	C
1,645	0,01	0,25

NOTE Cable performance between 1 MHz and 4 MHz is achieved by design only and it is therefore not necessary to test for this performance below 4 MHz.

The values in Table 4 are for information only:

Table 4 – Attenuation values

Frequency MHz	Maximum attenuation at 20 °C dB/100 m
4	3,5
10	5,4
16	6,8
31,25	9,6
62,5	13,7
100	17,5
200	25,3
300	31,5
600	46,3
900	58,3
1 000	62,0
1 200	69,0

6.3.4.2 ~~Environmental effects~~ Attenuation at elevated ambient temperatures

The increase in attenuation due to elevated temperature shall not be greater than 0,2 %/°C.

NOTE—The method for determining compliance with this requirement is under consideration.

6.3.5 Unbalance attenuation near-end (*TCL*, *EL TCL*)

The minimum unbalance attenuation near-end (transverse conversion loss or *TCL*) shall be equal to, or greater than, the value obtained from Formula (3) for all frequencies, *f*, in the frequency range from 1 MHz to ~~200~~ 250 MHz:

$$TCL = 40,0 - 10 \times \log_{10}(f) \quad [\text{dB}] \quad (3)$$

NOTE—The need for ELTCTL and TCL values above 200 MHz are under consideration.

NOTE 1 Values in the range 1 MHz to 30 MHz are equal to IEC 61156-5, Level 1.

TCL requirements for frequencies higher than 250 MHz may be defined in the detail specification.

NOTE 2 If the intention is to increase the frequency range of balance measurements, IEC TR 61156-1-2 provides guidance on the respective (e.g., balunless) measurement techniques.

The minimum equal-level far-end unbalance attenuation (equal-level transverse conversion transfer loss or *EL TCTL*) shall be equal to, or greater than, the value obtained from Formula (4) for all frequencies, f , in the range from 1 MHz to 30 MHz.

$$EL\ TCTL = 35,0 - 20 \times \log_{10}(f) \quad [\text{dB}] \quad (4)$$

NOTE 3 Values in the range 1 MHz to 30 MHz are equal to IEC 61156-5, Level 1.

EL TCTL requirements for frequencies higher than 30 MHz may be defined in the detail specification.

6.3.6 Near-end crosstalk ~~(NEXT)~~ (*PS NEXT*, *NEXT*)

~~When measured in accordance with IEC 61156-1,~~ The worst-pair power-sum near-end crosstalk, *PS NEXT*, of any pair for all frequencies in the range 4 MHz to 1 200 MHz shall be equal to, or greater than, the value obtained from Formula (5).

$$PS\ NEXT = 103,0 - 15 \times \log_{10}(f) \quad [\text{dB}] \quad (5)$$

where f is the frequency in MHz.

NOTE The cable performance between 1 MHz and 4 MHz is achieved by design only and it is therefore not necessary to test for this performance below 4 MHz.

The values given in Table 5 are for information only. For those frequencies where the calculated value of *PS NEXT* is greater than 75 dB, the requirement shall be 75 dB.

Table 5 – Near-end crosstalk, power-sum (*PS NEXT*)

Frequency MHz	Minimum <i>PS NEXT</i> dB
4	75
10	75
16	75
31,25	75
62,5	75
100	73
200	68
300	66
600	64
900	59
1 000	58
1 200	57

The minimum pair-to-pair *NEXT* for any pair combination shall be at least 3 dB better than the *PS NEXT* for any pair.

6.3.7 Far-end crosstalk ~~(FEXT)~~ (*PS ACR-F*, *ACR-F*)

~~When measured in accordance with IEC 61156-1, the worst pair-to-pair equal level far-end crosstalk, PS EL FEXT, of any pair shall not be less than the value obtained from equation (5) for all frequencies in the range from 4 MHz to 1 200 MHz.~~

~~$$PS\ EL\ FEXT(f) = 91 - 20 \times \log_{10}(f) \quad [dB] \quad (5)$$~~

~~where f is the frequency in MHz.~~

The worst-pair power-sum equal level far-end crosstalk, *PS ACR-F*, of any pair for all frequencies in the range 4 MHz to 1 200 MHz shall be equal to, or greater than, the value obtained from Formula (6).

$$PS\ ACR - F = 91 - 20 \times \log_{10}(f) \quad [dB] \quad (6)$$

where f is the frequency in MHz.

NOTE The cable performance between 1 MHz and 4 MHz is achieved by design only and it is therefore not necessary to test for this performance below 4 MHz

If *FEXT* loss is greater than 90 dB, calculation of *PS ACR-F* loss is not required.

The values given in Table 6 are for information only. For those frequencies where the calculated value of ~~PS EL FEXT~~ *PS ACR-F* is greater than 75 dB, the requirement shall be 75 dB.

Table 6 – Far-end crosstalk ~~(FEXT)~~ (*PS ACR-F*)

Frequency MHz	PS EL FEXT Minimum <i>PS ACR-F</i> dB for 100 m
4	75
10	71
16	67
31,25	61
62,5	55
100	51
200	45
300	41
600	35
900	32
1 000	31
1 200	29

The minimum pair-to-pair *ACR-F* for any pair combination shall be at least 3 dB better than the *PS ACR-F* for any pair.

6.3.8 Alien (exogenous) near-end crosstalk

Generally proven by design.

6.3.9 Alien (exogenous) far-end crosstalk

Generally proven by design.

6.3.10 Alien (exogenous) crosstalk of bundled cables

Generally proven by design.

6.3.11 Characteristic Impedance

~~3.3.6.1 Nominal impedance~~

~~Unless otherwise specified in the relevant detail specification, the nominal impedance of the cable shall be 100 Ω.~~

~~3.3.6.2 Mean characteristic impedance~~

~~When measured in accordance with 3.3.6.3, 3.3.6.3/3.3.6.2.3 or 3.3.6.3/3.3.6.2.3 to 3.3.6.2.5 of IEC 61156-1, the mean characteristic impedance shall be $\pm 5\%$ of the nominal impedance at 100 MHz.~~

The impedance requirement is specified as fitted or mean characteristic impedance at a certain frequency.

The impedance measured in accordance with IEC 61156-1 shall be $100\ \Omega \pm 5\ \Omega$ at 100 MHz.

The return loss shall also be measured.

Further background on the measurement of fitted and mean characteristic impedance can be found in IEC TR 61156-1-2. Recommendations given in IEC TR 61156-1-2 and IEC TR 61156-1-5 for improvement of measurement uncertainty should be considered.

6.3.12 Return loss (RL)

~~When measured in accordance with 3.3.7 of IEC 61156-1~~ The minimum return loss of any pair in the frequency range indicated in Table 7 shall be greater than the values in Table 7.

Table 7 – Return loss

Frequency range MHz	Minimum return loss dB
4 to 10	$20,0 + 5,0 \times \log_{10}(f)$
10 to 20	25,0
20 to 250	$25,0 - 7,0 \times \log_{10}(f/20)$
250 to 600	17,3
600 to 1 200	$17,3 - 10 \times \log_{10}(f/600)$

~~3.3.8 Screening attenuation~~

~~Screening attenuation is a part of the coupling attenuation. When measured separately, as per IEC 62153-4-2, the screening attenuation in the frequency range from 30,0 MHz to 1 200 MHz shall not be less than the 60 dB.~~

6.4 Mechanical and dimensional characteristics and requirements

6.4.1 Dimensional requirements

The diameter of insulation, the nominal thickness of the sheath and the ~~nominal~~ maximum overall diameter of the sheath are not specified, but shall be indicated in the relevant detail specification.

6.4.2 Elongation at break of the conductors

The minimum elongation at break of the conductor shall be ~~10~~ not less than 8 %.

6.4.3 Tensile strength of the insulation

The tensile strength of the insulation is not specified, but may be indicated in the relevant detail specification.

6.4.4 Elongation at break of the insulation

The minimum value of the elongation at break of the insulation shall be not less than 100 %.

6.4.5 Adhesion of the insulation to the conductor

The adhesion of the insulation to the conductor is not specified, but may be indicated in the relevant detail specification.

6.4.6 Elongation at break of the sheath

The minimum value of the elongation at break of the sheath shall be not less than 100 %.

6.4.7 Tensile strength of the sheath

The minimum tensile strength of the sheath shall be not less than 9 MPa.

6.4.8 Crush test of the cable

~~The crush test of the cable is not specified but may be indicated in the relevant detail specification.~~

The minimum force shall be 1 000 N.

6.4.9 Impact test of the cable

~~Not applicable.~~

The impact resistance of the cable is not specified but may be indicated in the relevant detail specification.

6.4.10 Bending under tension

~~The bending under tension test of the cable shall be performed using a diameter of the pulley of 120 mm (under consideration). The requirement shall be stated in the relevant detail specification.~~

The bending performance of the cable is not specified but shall be indicated in the relevant detail specification.

6.4.11 Repeated bending of the cable

Not applicable.

6.4.12 Tensile performance of the cable

~~During installation, the value of the pulling force shall not exceed 20 N per pair.~~

The tensile strength of the cable is not specified but may be indicated in the relevant detail specification.

6.4.13 Shock-test requirements of the cable

Not applicable.

6.4.14 Bump-test requirements of the cable

Not applicable.

6.4.15 Vibration-test requirements of the cable

Not applicable.

6.5 Environmental characteristics

6.5.1 Shrinkage of insulation

When tested at $(100 \pm 2) ^\circ\text{C}$ for 1 h, the shrinkage of the insulation shall ~~be less than, or equal to,~~ not exceed 5 %. The length of the sample shall be 150 mm, and the shrink-back shall be measured as the sum from both ends.

6.5.2 Wrapping test of insulation after thermal ageing

Not applicable.

6.5.3 Bending test of insulation at low temperature

The bending test of the insulated conductor shall be carried out at $(-20 \pm 2) ^\circ\text{C}$. The mandrel diameter shall be 6 mm. There shall be no cracks in the insulation.

6.5.4 Elongation at break of the sheath after ageing

The ageing regime shall be seven days at $(100 \pm 2) ^\circ\text{C}$. The elongation at break after ageing shall not be less than 50 % of the unaged value.

6.5.5 Tensile strength of the sheath after ageing

The ageing regime shall be seven days at $(100 \pm 2) ^\circ\text{C}$. The tensile strength after ageing shall be not less than 70 % of the unaged value.

6.5.6 Sheath pressure ~~test~~ at high temperature

Not applicable.

6.5.7 Cold bend test of the cable

The bending test shall be carried out at $(-20 \pm 2) ^\circ\text{C}$. The mandrel diameter shall be eight times the overall diameter of the cable. There shall be no cracks in the sheath.

6.5.8 ~~Heat~~ Hot shock test

Not applicable.

6.5.9 Damp heat steady state

Not applicable.

6.5.10 Solar radiation (UV)

The resistance to solar radiation is not specified but may be specified in the relevant detail specification.

6.5.11 Solvents and contaminating fluids

The resistance to solvents and contaminating fluids is not specified but may be specified in the relevant detail specification.

6.5.12 Salt mist and sulphur dioxide

Not applicable.

6.5.13 Water immersion

Not applicable.

6.5.14 Hygroscopicity

The amount of moisture gained after 3 h shall not exceed 1 % in weight.

6.5.15 Wicking

The test solution shall not wet the filter paper at the end of 6 h.

6.5.16 Flame propagation characteristics of a single cable

~~When required by local regulations~~ If indicated in the relevant detail specification, the test shall be performed in accordance with IEC 61156-1. Local regulations can apply.

6.5.17 Flame propagation characteristics of bunched cables

~~When required~~ If indicated in the relevant detail specification, the test shall be performed in accordance with IEC 61156-1. Local regulations can apply.

~~3.5.11 Acid gas evolution~~

~~When required, the test shall be performed in accordance with IEC 61156-1.~~

6.5.18 Resistance to fire

Not applicable.

6.5.19 Halogen gas evolution

If indicated in the relevant detail specification, the test shall be performed in accordance with IEC 61156-1. Local regulations can apply.

6.5.20 Smoke generation

~~When required, the test shall be performed in accordance with IEC 61156-1.~~

If indicated in the relevant detail specification, the test shall be performed in accordance with IEC 61156-1. Local regulations can apply.

6.5.21 Toxic gas emission

~~Under consideration.~~

If indicated in the relevant detail specification, the test shall be performed in accordance with IEC 61156-1. Local regulations can apply.

~~3.5.14 Combined flame and smoke test~~

~~Under consideration.~~

6.5.22 Integrated fire test

If indicated in the relevant detail specification, the test shall be performed in accordance with IEC 61156-1. Local regulations can apply.

7 Introduction to the blank detail specification

The blank detail specification for cables described in this document is ~~published as IEC 61156-7-1~~ given in Annex A and should be used to identify a specific product.

When completing the detail specification, the following information shall be supplied:

- a) conductor size and type;
- b) number of elements;
- c) cable construction details;
- d) nominal impedance of the cable;
- ~~d) flammability requirements;~~
- e) electrical requirements;
- f) transmission requirements;
- g) mechanical requirements;
- h) environmental requirements;
- i) fire performance.

Annex A (informative)

Blank detail specification

The blank detail specification determines the layout and style for detail specifications describing symmetrical pair/quad cables for digital communications. Detail specifications, based on the blank detail specification, may be prepared by a national organization, a manufacturer, or a user.

This blank detail specification includes additional recommended environmental characteristics and severities, which are derived from the environmental classifications that are specified for cabling for various environments.

NOTE Environmental classifications are presented in ISO/IEC 11801-1 with three levels of severity in four areas: mechanical, ingress, climatic, and electromagnetic; thus, in tabular form, they are referred to as the "MICE table".

The detail specification shall be written in accordance with the layout of the blank detail specification described here.

The numbers shown in square brackets in the following pages correspond to the following items of required information, which shall be entered in the spaces provided.

- [1] Name and address of the organization that has prepared the document.
- [2] IEC document number, issue number and date of issue.
- [3] Address of the organization from which the document is available.
- [4] Related documents.
- [5] Any other reference to the cable, national reference, trade name, etc.
- [6] A complete description of the cable including any distinguishing performance characteristics.
- [7] Details of the cable material and construction.
- [8] Special requirements for bending radius or operating temperatures.
- [9] List of cable characteristics. They are separated into electrical, transmission, mechanical and environmental characteristics.
- [10] Appropriate subclause references in the sectional specification IEC 61156-1.
- [11] Requirements applicable to this cable. The values entered shall meet as a minimum the requirements of the sectional specification IEC 61156-7.
- [12] Comments – Relevant remarks.

[1] Prepared by		[2] Document: Issue: Date:	
[3] Available from:		[4] Generic specification: IEC 61156-1 Sectional specification: IEC 61156-7 Blank detail specification: IEC 61156-7: 2023, Annex A	
[5] Additional information:			
[6] Cable description:			
[7] Cable construction:	IEC 61156-7:2023, subclause		[12] Comments
	5.2.2	Conductor:	
	5.2.3.1	Insulation material: Maximum diameter:	
	5.2.3.2	Colour code of insulation:	
	5.2.4.2	Screening of the cable element: Tape material Drain wire Braid wire Braid material	
	5.2.5	Cable make-up: Protective wrapping	
	5.2.6	Screening of the cable core: Tape material Minimum overlap Drain wire Braid wire Braid material	
	5.2.7	Sheath Material Nominal thickness Colour Maximum overall diameter Marking Ripcord	
	5.2.8	Identification	
5.2.9	Finished cable: Packaging		
[8] Minimum bending radius for static bending: Minimum bending radius for dynamic bending: Temperature range for installation: Operating temperature range under static conditions: C1: -10 °C to +60 °C C2: -25 °C to +70 °C C3: -40 °C to +70 °C			

[9] Characteristics	[10] IEC 611567:2023, subclause	[11]	[12] Comments
Electrical characteristics and tests	6.2		
Conductor resistance	6.2.1	$\leq \dots \Omega/\text{km}$	
Resistance unbalance within a pair	6.2.2	$\leq \dots \%$	
Dielectric strength:			
Conductor/conductor	6.2.3	$\dots \text{ kV DC/AC for } \dots \text{ min / } \dots \text{ s}$	
Conductor/screen	6.2.3	$\dots \text{ kV DC/AC for } \dots \text{ min / } \dots \text{ s}$	
Insulation resistance:			
Conductor/conductor	6.2.4	$\geq \dots \text{ M}\Omega \cdot \text{km}$	
Conductor/screen	6.2.4	$\geq \dots \text{ M}\Omega \cdot \text{km}$	
Mutual capacitance	6.2.5	$\leq \dots \text{ pF/m}$	
Capacitance unbalance pair to ground	6.2.6	$\leq \dots \text{ pF/m}$	
Transfer impedance	6.2.7		
Coupling attenuation	6.2.8		
Current-carrying capacity	6.2.9	$\dots \text{ mA}$	Respective installation conditions shall be specified
Resistance of the screen	6.2.10	$\leq \dots \text{ m}\Omega/\text{m}$	
Transmission characteristics	6.3		
Velocity of propagation	6.3.2		
Phase delay	6.3.3.1	$\leq \dots \text{ ns/100 m}$	
Differential phase delay (skew)	6.3.3.2	$\leq \dots \text{ ns/100 m}$	
Environmental temperature coefficient	6.3.3.3		
Attenuation	6.3.4		
Attenuation at 20 °C	6.3.4.1	$\leq \dots \text{ dB/100 m}$	
Attenuation at elevated temperature:			
Environmental temperature coefficient	6.3.4.2	$\leq \dots \text{ }^\circ\text{C}$	
Unbalance attenuation near-end (<i>TCL</i>)	6.3.5	$\geq \dots \text{ dB}$	
Unbalance attenuation far-end (<i>EL TCL</i>)	6.3.5	$\geq \dots \text{ dB}$	
Near-end crosstalk	6.3.6	$\geq \dots \text{ dB}$	
Attenuation to crosstalk ratio far-end	6.3.7	$\geq \dots \text{ dB}$	
Impedance	6.3.11		
Return loss	6.3.12	$\geq \dots \text{ dB}$	

[9] Characteristics	[10] IEC 61156-7:2023, subclause	[11]	[12] Comments
Mechanical and dimensional characteristics	6.4		
Dimensional requirements	6.4.1		
Insulation diameter		... mm	
Sheath thickness		... mm	
Overall sheath diameter		... mm	
Elongation at break of the conductors	6.4.2	≥ ...%	
Tensile strength of the insulation	6.4.3	≥ ...MPa	
Elongation at break of the insulation	6.4.4	≥ ...%	
Adhesion of the insulation to the conductor	6.4.5		
Elongation at break of the sheath	6.4.6	≥ ...%	
Tensile strength of the sheath	6.4.7	≥ ...MPa	
Crush test of the cable	6.4.8	≥ 1 000 N over 100 mm (linear) min.	Optional MICE levels: M1: ≥ 45 N over 25 mm (linear) min. M2: ≥ 1 100 N over 150 mm (linear) min. M3: ≥ 2 200 N over 150 mm (linear) min.
Impact test of the cable	6.4.9	≥ ... J	Optional MICE levels: M1: ≥ 1 J M2: ≥ 10 J M3: ≥ 30 J
Bending under tension	6.4.10		
Repeated bending	6.4.11	500 cycles, no cracking of the insulation or sheath or loss of continuity of the metallic components	
Tensile performance of the cable	6.4.12		
Shock test	6.4.13	Not applicable	
Bump test	6.4.14	Not applicable	
Vibration test	6.4.15	Not applicable	

[9] Characteristics	[10] IEC 611567:2023, subclause	[11]	[12] Comments
Environmental characteristics	6.5		
Shrinkage of insulation	6.5.1	≤ ... %	
Wrapping test of insulation after thermal ageing	6.5.2	Not applicable	
Bending test of insulation at low temperature	6.5.3		
Elongation at break of the sheath after ageing	6.5.4	≥ ...%	
Tensile strength of the sheath after ageing	6.5.5	≥ ...MPa	
Sheath pressure at high temperature	6.5.6	Not applicable	
Cold bend test of the cable	6.5.7		
Heat shock test	6.5.8	Not applicable	
Damp heat steady state	6.5.9	Not applicable	
Solar radiation	6.5.10		Optional MICE levels: C1: not applicable C2, C3: under consideration
Solvents and contaminating fluids	6.5.11		
Salt mist and sulphur dioxide test	6.5.12	Not applicable	
Water immersion test	6.5.13	Not applicable	
Hygroscopicity	6.5.14		
Wicking	6.5.15		
Flame propagation characteristics of a single cable	6.5.16		
Flame propagation characteristics of bunched cables	6.5.17		
Halogen gas evolution	6.5.19		
Smoke generation	6.5.20		The requirement and the test method shall be specified in the detailed specification.
Toxic gas emission	6.5.21		
Integrated fire test	6.5.22		
When a characteristic applies but a specific value is not considered necessary, then NS for Not Specified should be entered at the appropriate place. When NS is used, the appropriate requirements in the specification should apply. ESD requirements are considered not applicable. NOTE 1 When a characteristic is marked as not applicable, it is not required by Clause 4 to Clause 7 of this document but can be required in the detail specification. NOTE 2 Ingress requirements using particles are not applicable to a cable. NOTE 3 Electromagnetic requirements follow the MICE scheme given in ISO/IEC 11801-1:2017, 6.2.2; they have been dealt with by using the requirements that are given for transfer impedance and coupling attenuation. NOTE 4 The proposed severities follow the MICE scheme of ISO/IEC 11801-1:2017, 6.2.2. Depending on the actual need of end users, other severities can be agreed between customer and suppliers.			

Bibliography

IEC TR 61156-1-2, *Multicore and symmetrical pair/quad cables for digital communications – Part 1-2: Electrical transmission characteristics and test methods of symmetrical pair/quad cables*

IEC 61156-1-4, *Multicore and symmetrical pair/quad cables for digital communications – Part 1-4: Assessment of conductor heating in bundled cables due to the deployment of remote powering*

IEC TR 61156-1-5, *Multicore and symmetrical pair/quad cables for digital communications – Part 1-5: Correction procedures for the measurement results of return loss and input impedance*

IEC 61156-5, *Multicore and symmetrical pair/quad cables for digital communications – Part 5: Symmetrical pair/quad cables with transmission characteristics up to 1 000 MHz – Horizontal floor wiring – Sectional specification*

ISO/IEC 11801-1:2017, *Information technology – Generic cabling for customer premises – Part 1: General requirements*

ISO/IEC TR 29106, *Information technology – Generic cabling – Introduction to the MICE environmental classification*

ISO/IEC TS 29125, *Information technology – Telecommunications cabling requirements for remote powering of terminal equipment*

IECNORM.COM : Click to view the full PDF of IEC 61156-7:2023 RLV

INTERNATIONAL STANDARD

**Multicore and symmetrical pair/quad cables for digital communications –
Part 7: Symmetrical pair cables with transmission characteristics up to
1 200 MHz – Sectional specification for digital and analogue communication
cables**

IECNORM.COM : Click to view the full PDF of IEC 61156-7:2023 RLV

CONTENTS

FOREWORD.....	5
1 Scope.....	7
2 Normative references	7
3 Terms and definitions	7
4 Installation consideration	8
4.1 General remarks	8
4.2 Bending radius of installed cable.....	8
4.3 Climatic conditions.....	8
5 Material and cable construction	8
5.1 General remarks	8
5.2 Cable construction	8
5.2.1 General	8
5.2.2 Conductor.....	8
5.2.3 Insulation.....	9
5.2.4 Cable element	9
5.2.5 Cable make-up	9
5.2.6 Screening of the cable core	9
5.2.7 Sheath.....	9
5.2.8 Identification.....	10
5.2.9 Finished cable	10
6 Characteristics and requirements	10
6.1 General remarks	10
6.2 Electrical characteristics and tests	10
6.2.1 Conductor resistance	10
6.2.2 Resistance unbalance within a pair.....	10
6.2.3 Dielectric strength.....	10
6.2.4 Insulation resistance.....	11
6.2.5 Mutual capacitance.....	11
6.2.6 Capacitance unbalance pair to ground	11
6.2.7 Transfer impedance	11
6.2.8 Coupling attenuation.....	11
6.2.9 Current-carrying capacity.....	12
6.2.10 Resistance of the screen	12
6.3 Transmission characteristics	12
6.3.1 General remark.....	12
6.3.2 Velocity of propagation (phase velocity).....	12
6.3.3 Phase delay and differential phase delay (delay skew)	12
6.3.4 Attenuation (α).....	13
6.3.5 Unbalance attenuation near-end (TCL , $EL\ TCL$).....	13
6.3.6 Near-end crosstalk ($PS\ NEXT$, $NEXT$).....	14
6.3.7 Far-end crosstalk ($PS\ ACR-F$, $ACR-F$)	15
6.3.8 Alien (exogenous) near-end crosstalk	16
6.3.9 Alien (exogenous) far-end crosstalk	16
6.3.10 Alien (exogenous) crosstalk of bundled cables	16
6.3.11 Impedance.....	16
6.3.12 Return loss (RL).....	16

6.4	Mechanical and dimensional characteristics and requirements	17
6.4.1	Dimensional requirements	17
6.4.2	Elongation at break of the conductors	17
6.4.3	Tensile strength of the insulation	17
6.4.4	Elongation at break of the insulation	17
6.4.5	Adhesion of the insulation to the conductor	17
6.4.6	Elongation at break of the sheath	17
6.4.7	Tensile strength of the sheath	17
6.4.8	Crush test of the cable	17
6.4.9	Impact test of the cable	17
6.4.10	Bending under tension	18
6.4.11	Repeated bending of the cable	18
6.4.12	Tensile performance of the cable	18
6.4.13	Shock-test requirements of the cable	18
6.4.14	Bump-test requirements of the cable	18
6.4.15	Vibration-test requirements of the cable	18
6.5	Environmental characteristics	18
6.5.1	Shrinkage of insulation	18
6.5.2	Wrapping test of insulation after thermal ageing	18
6.5.3	Bending test of insulation at low temperature	18
6.5.4	Elongation at break of the sheath after ageing	18
6.5.5	Tensile strength of the sheath after ageing	18
6.5.6	Sheath pressure at high temperature	18
6.5.7	Cold bend test of the cable	19
6.5.8	Hot shock test	19
6.5.9	Damp heat steady state	19
6.5.10	Solar radiation (UV)	19
6.5.11	Solvents and contaminating fluids	19
6.5.12	Salt mist and sulphur dioxide	19
6.5.13	Water immersion	19
6.5.14	Hygroscopicity	19
6.5.15	Wicking	19
6.5.16	Flame propagation characteristics of a single cable	19
6.5.17	Flame propagation characteristics of bunched cables	19
6.5.18	Resistance to fire	19
6.5.19	Halogen gas evolution	19
6.5.20	Smoke generation	20
6.5.21	Toxic gas emission	20
6.5.22	Integrated fire test	20
7	Introduction to the blank detail specification	20
	Annex A (informative) Blank detail specification	21
	Bibliography	26
	Table 1 – Transfer impedance	11
	Table 2 – Coupling attenuation	11
	Table 3 – Attenuation, constant values	13
	Table 4 – Attenuation values	13
	Table 5 – Near-end crosstalk, power-sum (<i>PS NEXT</i>)	15

Table 6 – Far-end crosstalk ($PS\ ACR-F$)	16
Table 7 – Return loss	17

IECNORM.COM : Click to view the full PDF of IEC 61156-7:2023 RLV

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**MULTICORE AND SYMMETRICAL PAIR/QUAD CABLES
FOR DIGITAL COMMUNICATIONS –****Part 7: Symmetrical pair cables with transmission
characteristics up to 1 200 MHz –
Sectional specification for digital and analogue
communication cables**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 61156-7 has been prepared by subcommittee 46C: Wires and symmetrical cables, of IEC technical committee 46: Cables, wires, waveguides, RF connectors, RF and microwave passive components and accessories. It is an International Standard.

This part of IEC 61156 is to be read in conjunction with IEC 61156-1:2023.

This second edition cancels and replaces the first edition published in 2003 and Amendment 1:2012. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) restructure all text to comply with ISO/IEC Directives Part 2;

- b) align clauses with IEC 61156-1:2023;
- c) remove the clause related to screening attenuation as it is no longer a test to be performed (replaced by coupling attenuation);
- d) replace the IEC 62153-4-2 method (injection clamp) with IEC 61156-4-5 (absorbing clamp) for coupling attenuation measurement to be consistent with all other parts of the IEC 61156 series;
- e) include IEC 62153-4-9 test method (triaxial) for coupling attenuation measurement to be consistent with all other parts of the IEC 61156 series;
- f) incorporate the blank detail specification.

The text of this International Standard is based on the following documents:

Draft	Report on voting
46C/1228/CDV	46C/1233/RVC

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

A list of all parts in the IEC 61156 series, published under the general title *Multicore and symmetrical pair/quad cables for digital communications*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

MULTICORE AND SYMMETRICAL PAIR/QUAD CABLES FOR DIGITAL COMMUNICATIONS –

Part 7: Symmetrical pair cables with transmission characteristics up to 1 200 MHz – Sectional specification for digital and analogue communication cables

1 Scope

This part of IEC 61156 specifies cables that can be used for various communication systems as well as for analogue systems, such as video, that exist or are under development and which may use as many as four pairs simultaneously. In this sense, this sectional specification provides the cable characteristics required by system developers to evaluate new systems as well as to enhance present systems.

It covers a cable having four individually screened (S/FTP) pairs. The cable can be provided with a common screen over the cable core.

The transmission characteristics are specified up to a frequency of 1 200 MHz and at a temperature of 20 °C.

The cables covered by this sectional specification are intended to operate with voltages and currents normally encountered in communication systems and support the delivery of DC low voltage remote powering applications. These cables are not intended to be used in conjunction with low impedance sources, for example the electric power supply of public utility mains.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60304, *Standard colours for insulation for low-frequency cables and wires*

IEC 61156-1, *Multicore and symmetrical pair/quad cables for digital communications – Part 1: Generic specification*

IEC 62153-4-3, *Metallic communication cable test methods – Part 4-3: Electromagnetic compatibility (EMC) – Surface transfer impedance – Triaxial method*

IEC 62153-4-5, *Metallic communication cable test methods – Part 4-5: Electromagnetic compatibility (EMC) – Screening or coupling attenuation – Absorbing clamp method*

IEC 62153-4-9, *Metallic communication cable test methods – Part 4-9: Electromagnetic compatibility (EMC) – Coupling attenuation of screened balanced cables, triaxial method*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 61156-1 apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- IEC Electropedia: available at <https://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

4 Installation consideration

4.1 General remarks

Installation considerations are defined in IEC 61156-1.

4.2 Bending radius of installed cable

The bending radius of the installed cable shall not be less than 4 times the outside diameter of the cable.

4.3 Climatic conditions

Under static conditions, the cables shall operate in the temperature range from –20 °C to +60 °C. The temperature dependence of the cables is specified for screened cables and should be taken into account for the design of actual cabling systems.

The recommended temperature range during installation should be indicated in the relevant detail specification.

When applications demand remote powering, the maximum temperature of the conductor shall not exceed the maximum operating temperature of the cable. Dielectric performance can be changed permanently due to over exposure of high temperatures.

5 Material and cable construction

5.1 General remarks

The choice of materials and cable construction shall be suitable for the intended application and installation of the cable. Particular care should be taken to meet any special requirements for fire performance (such as burning properties, smoke generation, evolution of halogen gas, etc.) and remote powering.

5.2 Cable construction

5.2.1 General

The cable construction shall be in accordance with the materials, dimensions and assembly details given in the relevant detail specification.

5.2.2 Conductor

The conductor shall be a solid annealed copper conductor, in accordance with IEC 61156-1, and should have a nominal diameter between 0,5 mm and 0,65 mm.

A conductor diameter of up to 0,8 mm may be used.

5.2.3 Insulation

5.2.3.1 Insulation material

The conductor shall be insulated with a suitable thermoplastic material. Examples of suitable materials are:

- polyolefin;
- fluoropolymer;
- low-smoke halogen-free thermoplastic material.

The insulation may be solid or cellular with or without a solid dielectric skin. The insulation shall be continuous and shall have a thickness such that the completed cable meets the specified requirements. The nominal thickness of the insulation shall be compatible with the method of conductor termination.

5.2.3.2 Colour code of insulation

The colour code is not specified but shall be indicated in the relevant detail specification. The colours shall be readily identifiable and shall correspond reasonably with the standard colours shown in IEC 60304.

NOTE It is acceptable to mark or stripe the "a" wire with the colour of the "b" wire to facilitate pair identification.

5.2.4 Cable element

5.2.4.1 Cable element type

The cable element shall be a screened twisted pair.

5.2.4.2 Screening of the cable element

The screen for the cable element shall be in accordance with IEC 61156-1. If a braid is used, the minimum braid coverage shall be such as to meet the screening requirements of this document. The individual components used to screen the cable element shall be in electrical contact.

5.2.5 Cable make-up

The cable elements shall be assembled to form the cable core.

The core of the cable may be wrapped with a protective layer of non-hygroscopic and non-wicking material.

5.2.6 Screening of the cable core

A screen for the cable core may be provided. The screen shall be in accordance with IEC 61156-1.

5.2.7 Sheath

The sheath material shall consist of a suitable thermoplastic material.

Examples of suitable materials are:

- polyolefin;
- PVC;
- fluoropolymer;
- low-smoke halogen-free thermoplastic material.

The sheath shall be continuous, having a thickness as uniform as possible. A non-metallic ripcord may be provided. When provided, the ripcord shall be non-hygroscopic and non-wicking.

The colour of the sheath is not specified but should be specified in the relevant detail specification.

5.2.8 Identification

5.2.8.1 Cable marking

Each length of cable shall bear the name of the supplier and the cable type and, when provided, the year of manufacture, using one of the following methods:

- a) coloured threads or tapes;
- b) printed tape;
- c) printing on the cable core wrapping;
- d) marking on the sheath.

Additional markings, such as length marking, etc., are permitted. If used, such markings should be indicated in the relevant detail specification.

5.2.8.2 Labelling

The following information shall be provided either on a label attached to each length of finished cable or on the outside of the product package:

- a) type of cable;
- b) supplier's name or logo;
- c) year of manufacture;
- d) length of cable in metres.

5.2.9 Finished cable

The finished cable shall be adequately protected for storage and shipment.

6 Characteristics and requirements

6.1 General remarks

Clause 6 lists the characteristics and minimum requirements of a cable complying with this document. Test methods shall be in accordance with IEC 61156-1.

6.2 Electrical characteristics and tests

6.2.1 Conductor resistance

The maximum conductor resistance shall not exceed 8,5 Ω /100 m of cable.

6.2.2 Resistance unbalance within a pair

The resistance unbalance within a pair shall not exceed 2,0 %.

6.2.3 Dielectric strength

The test shall be performed on conductor/conductor and conductor/screen with 1,0 kV DC for 1 min or, alternately, with 2,5 kV DC for 2 s.

An AC voltage may be used. The AC voltage levels in these cases shall be 0,7 kV AC for 1 min or, alternately, 1,7 kV AC for 2 s.

When installed in conjunction with power cables, local regulations may require a higher test voltage

6.2.4 Insulation resistance

The test, immediately after the dielectric strength test, shall be performed on:

- conductor/conductor;
- conductor/screen.

The minimum insulation resistance at 20 °C shall not be less than 5 000 MΩ·km.

6.2.5 Mutual capacitance

The mutual capacitance is not specified but may be indicated in the relevant detail specification.

6.2.6 Capacitance unbalance pair to ground

The maximum capacitance unbalance pair to ground shall not exceed 1 200 pF/km at a frequency of 1 kHz.

6.2.7 Transfer impedance

When measured using the triaxial method (IEC 62153-4-3), the transfer impedance shall not exceed the values listed in Table 1 at the indicated frequencies.

Table 1 – Transfer impedance

Frequency range MHz	Maximum surface transfer impedance mΩ/m
1 to 10	10
10 to 100	$10 \times f/10$
NOTE Values in the range 10 MHz to 100 MHz are equal to IEC 61156-5, Grade 1.	

6.2.8 Coupling attenuation

When measured using the absorbing clamp method (IEC 62153-4-5) or the triaxial method (IEC 62153-4-9), the coupling attenuation in the frequency range from 30 MHz to 1 200 MHz shall meet the requirements indicated in Table 2.

Table 2 – Coupling attenuation

Frequency range MHz	Minimum coupling attenuation dB
30 to 100	85,0
100 to 1 200	$85,0 - 20 \times \log_{10}(f/100)$

NOTE Values in the range 30 MHz to 1 000 MHz are equal to IEC 61156-5, Type I.

6.2.9 Current-carrying capacity

The maximum current-carrying capacity is not specified but may be indicated in the relevant detail specification. Further guidance with respect to current carrying capacity is provided by ISO/IEC TS 29125 and the test method described in IEC 61156-1-4.

6.2.10 Resistance of the screen

The maximum longitudinal DC resistance value of the individual screens or an overall screen shall be less than 15 mΩ/m.

6.3 Transmission characteristics

6.3.1 General remark

All the tests shall be carried out on a cable length of 100 m, unless otherwise specified.

6.3.2 Velocity of propagation (phase velocity)

The minimum velocity of propagation for any screened cable element shall be equal to, or greater than, $0,6 \times c$ (c is the speed of light in vacuum) for all frequencies between 4 MHz and 1 200 MHz.

NOTE The velocity of propagation, group velocity and phase velocity are approximately equal for frequencies greater than 4 MHz when measured on symmetric cables, i.e. when the cables are operated in a balanced mode.

6.3.3 Phase delay and differential phase delay (delay skew)

6.3.3.1 Phase delay

The phase delay, τ , shall not exceed the value obtained from:

$$\tau = 500 + \frac{36}{\sqrt{f}} \quad [\text{ns} / 100 \text{ m}] \quad (1)$$

where

τ is the phase delay in ns/100 m;

f is the frequency in MHz.

6.3.3.2 Differential phase delay (delay skew)

Differential phase delay (delay skew) is the difference in phase delay between any two screened cable elements.

When the phase delay is measured at $-20\text{ °C} \pm 2\text{ °C}$, $20\text{ °C} \pm 3\text{ °C}$ and $60\text{ °C} \pm 1\text{ °C}$, the maximum differential phase delay (delay skew) at a given temperature shall not be greater than 25,0 ns/100 m in the frequency range from 4 MHz to 1 200 MHz.

6.3.3.3 Environmental effects

The differential delay (delay skew) due to temperature shall not vary by more than ± 10 ns/100 m over the temperature range from -20 °C to $+60\text{ °C}$ while still meeting the differential phase delay (delay skew) of 6.3.3.2.

6.3.4 Attenuation (α)

6.3.4.1 Attenuation at 20 °C operating temperature

The maximum attenuation α of any pair in the frequency range 4 MHz to 1 200 MHz shall be less than, or equal to, the value obtained from Formula (2) using the corresponding values of the constants given in Table 3.

$$\alpha = A \times \sqrt{f} + B \times f + \frac{C}{\sqrt{f}} \quad [\text{dB} / 100 \text{ m}] \quad (2)$$

Table 3 – Attenuation, constant values

Constants		
A	B	C
1,645	0,01	0,25

NOTE Cable performance between 1 MHz and 4 MHz is achieved by design only and it is therefore not necessary to test for this performance below 4 MHz.

The values in Table 4 are for information only:

Table 4 – Attenuation values

Frequency MHz	Maximum attenuation at 20 °C dB/100 m
4	3,5
10	5,4
16	6,8
31,25	9,6
62,5	13,7
100	17,5
200	25,3
300	31,5
600	46,3
900	58,3
1 000	62,0
1 200	69,0

6.3.4.2 Attenuation at elevated ambient temperatures

The increase in attenuation due to elevated temperature shall not be greater than 0,2 %/°C.

6.3.5 Unbalance attenuation near-end (TCL , $EL\ TCTL$)

The minimum unbalance attenuation near-end (transverse conversion loss or TCL) shall be equal to, or greater than, the value obtained from Formula (3) for all frequencies, f , in the frequency range from 1 MHz to 250 MHz:

$$TCL = 40,0 - 10 \times \log_{10}(f) \quad [\text{dB}] \quad (3)$$

NOTE 1 Values in the range 1 MHz to 30 MHz are equal to IEC 61156-5, Level 1.

TCL requirements for frequencies higher than 250 MHz may be defined in the detail specification.

NOTE 2 If the intention is to increase the frequency range of balance measurements, IEC TR 61156-1-2 provides guidance on the respective (e.g., balunless) measurement techniques.

The minimum equal-level far-end unbalance attenuation (equal-level transverse conversion transfer loss or *EL TCTL*) shall be equal to, or greater than, the value obtained from Formula (4) for all frequencies, *f*, in the range from 1 MHz to 30 MHz.

$$EL \ TCTL = 35,0 - 20 \times \log_{10}(f) \quad [\text{dB}] \quad (4)$$

NOTE 3 Values in the range 1 MHz to 30 MHz are equal to IEC 61156-5, Level 1.

EL TCTL requirements for frequencies higher than 30 MHz may be defined in the detail specification.

6.3.6 Near-end crosstalk (*PS NEXT*, *NEXT*)

The worst-pair power-sum near-end crosstalk, *PS NEXT*, of any pair for all frequencies in the range 4 MHz to 1 200 MHz shall be equal to, or greater than, the value obtained from Formula (5).

$$PS \ NEXT = 103,0 - 15 \times \log_{10}(f) \quad [\text{dB}] \quad (5)$$

where *f* is the frequency in MHz.

NOTE The cable performance between 1 MHz and 4 MHz is achieved by design only and it is therefore not necessary to test for this performance below 4 MHz.

The values given in Table 5 are for information only. For those frequencies where the calculated value of *PS NEXT* is greater than 75 dB, the requirement shall be 75 dB.

Table 5 – Near-end crosstalk, power-sum (*PS NEXT*)

Frequency MHz	Minimum <i>PS NEXT</i> dB
4	75
10	75
16	75
31,25	75
62,5	75
100	73
200	68
300	66
900	59
1 000	58
1 200	57

The minimum pair-to-pair *NEXT* for any pair combination shall be at least 3 dB better than the *PS NEXT* for any pair.

6.3.7 Far-end crosstalk (*PS ACR-F*, *ACR-F*)

The worst-pair power-sum equal level far-end crosstalk, *PS ACR-F*, of any pair for all frequencies in the range 4 MHz to 1 200 MHz shall be equal to, or greater than, the value obtained from Formula (6).

$$PS\ ACR-F = 91 - 20 \times \log_{10}(f) \quad [\text{dB}] \quad (6)$$

where f is the frequency in MHz.

NOTE The cable performance between 1 MHz and 4 MHz is achieved by design only and it is therefore not necessary to test for this performance below 4 MHz.

If *FEXT* loss is greater than 90 dB, calculation of *PS ACR-F* loss is not required.

The values given in Table 6 are for information only. For those frequencies where the calculated value of *PS ACR-F* is greater than 75 dB, the requirement shall be 75 dB.

Table 6 – Far-end crosstalk (*PS ACR-F*)

Frequency MHz	Minimum <i>PS ACR-F</i> dB for 100 m
4	75
10	71
16	67
31,25	61
62,5	55
100	51
200	45
300	41
600	35
900	32
1 000	31
1 200	29

The minimum pair-to-pair *ACR-F* for any pair combination shall be at least 3 dB better than the *PS ACR-F* for any pair.

6.3.8 Alien (exogenous) near-end crosstalk

Generally proven by design.

6.3.9 Alien (exogenous) far-end crosstalk

Generally proven by design.

6.3.10 Alien (exogenous) crosstalk of bundled cables

Generally proven by design.

6.3.11 Impedance

The impedance requirement is specified as fitted or mean characteristic impedance at a certain frequency.

The impedance measured in accordance with IEC 61156-1 shall be $100\ \Omega \pm 5\ \Omega$ at 100 MHz.

The return loss shall also be measured.

Further background on the measurement of fitted and mean characteristic impedance can be found in IEC TR 61156-1-2. Recommendations given in IEC TR 61156-1-2 and IEC TR 61156-1-5 for improvement of measurement uncertainty should be considered.

6.3.12 Return loss (*RL*)

The minimum return loss of any pair in the frequency range indicated in Table 7 shall be greater than the values in Table 7.