

INTERNATIONAL STANDARD

NORME INTERNATIONALE



Railway applications – Rolling stock equipment – Shock and vibration tests

Applications ferroviaires – Matériel roulant – Essais de chocs et vibrations

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

PRICE CODE
CODE PRIX



ICS 45.060

ISBN 978-2-88910-944-9

CONTENTS

FOREWORD.....	4
INTRODUCTION.....	6
1 Scope.....	7
2 Normative references.....	8
3 Terms and definitions	9
4 General	10
5 Order of testing.....	11
6 Reference information required by the test house.....	11
6.1 Method of mounting and orientation of equipment under test.....	11
6.2 Reference and check points.....	11
6.2.1 Fixing point.....	11
6.2.2 Check point	12
6.2.3 Reference point	12
6.2.4 Measuring point	12
6.3 Mechanical state and functioning during test	12
6.3.1 Mechanical state.....	12
6.3.2 Functional tests	13
6.3.3 Performance tests.....	13
6.4 Reproducibility for random vibration tests.....	13
6.4.1 Acceleration spectral density (ASD)	13
6.4.2 Root mean square value (r.m.s.)	13
6.4.3 Probability density function (PDF)	13
6.4.4 Duration.....	13
6.5 Measuring tolerances.....	14
6.6 Recovery	14
7 Initial measurements and preconditioning.....	14
8 Functional random vibration test conditions	14
8.1 Test severity and frequency range	14
8.2 Duration of functional vibration tests	15
8.3 Functioning during test	15
9 Simulated long-life testing at increased random vibration levels.....	15
9.1 Test severity and frequency range	15
9.2 Duration of accelerated vibration tests	15
10 Shock testing conditions	16
10.1 Pulse shape and tolerance.....	16
10.2 Velocity changes	16
10.3 Mounting	16
10.4 Repetition rate	16
10.5 Test severity, pulse shape and direction.....	16
10.6 Number of shocks.....	17
10.7 Functioning during test	17
11 Transportation and handling.....	17
12 Final measurements	17
13 Acceptance criteria	17
14 Report	17

15	Test certificate	18
16	Disposal	18
Annex A (informative) Explanation of service measurements, measuring positions, methods of recording service data, summary of service data, and method used to obtain random test levels from acquired service data		25
Annex B (informative) Figure identifying general location of equipment on railway vehicles and their resulting test category		32
Annex C (informative) Example of a type test certificate		33
Annex D (informative) Guidance for calculating RMS values from ASD values or levels.....		34
Figure 1 – Gaussian distribution		9
Figure 2 – Category 1 – Class A – Body-mounted – ASD spectrum		19
Figure 3 – Category 1 – Class B – Body-mounted – ASD spectrum		20
Figure 4 – Category 2 – Bogie mounted – ASD spectrum		21
Figure 5 – Category 3 – Axle mounted – ASD spectrum		22
Figure 6 – Cumulative PDF tolerance bands		23
Figure 7 – Shock test tolerance – Bands half sine pulse		24
Figure A.1 – Standard measuring positions used for axle, bogie (frame) and body		25
Figure A.2 – Typical fatigue strength curve		29
Figure B.1 – General location of equipment on vehicles		32
Figure D.1 – ASD spectrum		35
Table 1 – Test severity and frequency range for functional random vibration tests.....		14
Table 2 – Test severity and frequency range.....		15
Table 3 – Test severity, pulse shape and direction.....		16
Table A.1 – Environment data acquisition summary of the test parameters/conditions.....		26
Table A.2 – Summary of the r.m.s. acceleration levels obtained from the questionnaire		28
Table A.3 – Test levels obtained from service data using the method shown in Clause A.4		31

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**RAILWAY APPLICATIONS –
ROLLING STOCK EQUIPMENT –
SHOCK AND VIBRATION TESTS**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61373 has been prepared by IEC technical committee 9: Electrical equipment and systems for railways.

This second edition cancels and replaces the first edition, issued in 1999 and constitutes a technical revision.

The main technical changes with regard to the previous edition are as follows:

- change of the method to calculate the acceleration ratio which has to be applied to the functional ASD value to obtain the simulated long-life ASD value;
- addition of the notion of partially certified against this standard;
- suppression of Annex B of the first edition due to the new method to calculate the acceleration ratio;
- addition of guidance for calculating the functional RMS value from service data or the RMS value from ASD levels of Figures 2 to 5.

The text of this standard is based on the following documents:

FDIS	Report on voting
9/1386/FDIS	9/1397/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

IECNORM.COM : Click to view the full PDF of IEC 61373 ed 2.0 :2010

INTRODUCTION

This standard covers the requirements for random vibration and shock testing items of pneumatic, electrical and electronic equipment/components (hereinafter only referred to as equipment) to be fitted on to railway vehicles. Random vibration is the only method to be used for equipment/component approval.

The tests contained within this standard are specifically aimed at demonstrating the ability of the equipment under test to withstand the type of environmental vibration conditions normally expected for railway vehicles. In order to achieve the best representation possible, the values quoted in this standard have been derived from actual service measurements submitted by various bodies from around the world.

This standard is not intended to cover self-induced vibrations as these will be specific to particular applications.

Engineering judgement and experience is required in the execution and interpretation of this standard.

This standard is suitable for design and validation purposes; however, it does not exclude the use of other development tools (such as sine sweep), which may be used to ensure a predetermined degree of mechanical and operational confidence. The test levels to be applied to the equipment under test are dictated only by its location on the train (i.e. axle, bogie or body-mounted).

It should be noted that these tests may be performed on prototypes in order to gain design information about the product performance under random vibration. However, for test certification purposes the tests have to be carried out on equipment taken from normal production.

IECNORM.COM : Click to view the full PDF of IEC 61373 ed 2.0:2010

RAILWAY APPLICATIONS – ROLLING STOCK EQUIPMENT – SHOCK AND VIBRATION TESTS

1 Scope

This International Standard specifies the requirements for testing items of equipment intended for use on railway vehicles which are subsequently subjected to vibrations and shock owing to the nature of railway operational environment. To gain assurance that the quality of the equipment is acceptable, it has to withstand tests of reasonable duration that simulate the service conditions seen throughout its expected life.

Simulated long-life testing can be achieved in a number of ways each having their associated advantages and disadvantages, the following being the most common:

- a) amplification: where the amplitudes are increased and the time base decreased;
- b) time compression: where the amplitude history is retained and the time base is decreased (increase of the frequency);
- c) decimation: where time slices of the historical data are removed when the amplitudes are below a specified threshold value.

The amplification method as stated in a) above, is used in this standard and together with the publications referred to in Clause 2; it defines the default test procedure to be followed when vibration testing items for use on railway vehicles. However, other standards exist and may be used with prior agreement between the manufacturer and the customer. In such cases test certification against this standard will not apply. Where service information is available tests can be performed using the method outlined in Annex A. If the levels are lower than those quoted in this standard, equipment is partially certified against this standard (only for service conditions giving functional test values lower than or equal to those specified in the test report).

Whilst this standard is primarily concerned with railway vehicles on fixed rail systems, its wider use is not precluded. For systems operating on pneumatic tyres, or other transportation systems such as trolleybuses, where the level of shock and vibration clearly differ from those obtained on fixed rail systems, the supplier and customer can agree on the test levels at the tender stage. It is recommended that the frequency spectra and the shock duration/amplitude be determined using the guidelines in Annex A. Equipment tested at levels lower than those quoted in this standard cannot be fully certified against the requirements of this standard.

An example of this is trolleybuses, whereby body-mounted trolleybus equipment could be tested in accordance with category 1 equipment referred to in the standard.

This standard applies to single axis testing. However multi-axis testing may be used with prior agreement between the manufacturer and the customer.

The test values quoted in this standard have been divided into three categories dependent only upon the equipment's location within the vehicle.

Category 1 Body mounted

Class A Cubicles, subassemblies, equipment and components mounted directly on or under the car body.

Class B Anything mounted inside an equipment case which is in turn mounted directly on or under the car body.

NOTE 1 Class B should be used when it is not clear where the equipment is to be located.

Category 2 Bogie mounted

Cubicles, subassemblies, equipment and components which are to be mounted on the bogie of a railway vehicle.

Category 3 Axle mounted

Subassemblies, equipment and components or assemblies which are to be mounted on the wheelset assembly of a railway vehicle.

NOTE 2 In the case of equipment mounted on vehicles with one level of suspension such as wagons and trucks, unless otherwise agreed at the tender stage, axle mounted equipment will be tested as category 3, and all other equipment will be tested as category 2.

The cost of testing is influenced by the weight, shape and complexity of the equipment under test. Consequently at the tender stage the supplier may propose a more cost-effective method of demonstrating compliance with the requirements of this standard. Where alternative methods are agreed it will be the responsibility of the supplier to demonstrate to his customer or his representative that the objective of this standard has been met. If an alternative method of evaluation is agreed, then the equipment tested cannot be certified against the requirement of this standard.

This standard is intended to evaluate equipment which is attached to the main structure of the vehicle (and/or components mounted thereon). It is not intended to test equipment which forms part of the main structure. Main structure in the sense of this standard means car body, bogie and axle. There are a number of cases where additional or special vibration tests may be requested by the customer, for example:

- a) equipment mounted on, or linked to, items which are known to produce fixed frequency excitation;
- b) equipment such as traction motors, pantographs, shoe gear, or suspension components which may be subjected to tests in accordance with their special requirements, applicable to their use on railway vehicles. In all such cases the tests carried out should be dealt with by separate agreement at the tender stage;
- c) equipment intended for use in special operational environments as specified by the customer.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60068-2-27:2008, *Environmental testing – Part 2-27: Tests – Test Ea and guidance: Shock*

IEC 60068-2-47:2005, *Environmental testing – Part 2-47: Tests – Mounting of specimens for vibration, impact and similar dynamic tests*

IEC 60068-2-64:2008, *Environmental testing – Part 2-64: Tests – Test Fh: Vibration, broadband random and guidance*

ISO 3534-1:2006, *Statistics – Vocabulary and symbols – Part 1: Probability and general statistical terms*

SOMMAIRE

AVANT-PROPOS	38
INTRODUCTION	40
1 Domaine d'application	41
2 Références normatives	42
3 Termes et définitions	43
4 Généralités	44
5 Ordre des essais	45
6 Informations de référence exigées par le laboratoire d'essai	45
6.1 Méthode de fixation et d'orientation des matériels soumis aux essais	45
6.2 Points de référence et de vérification	45
6.2.1 Point de fixation	46
6.2.2 Point de vérification	46
6.2.3 Point de référence	46
6.2.4 Point de mesure	46
6.3 Etat mécanique et fonctionnement pendant l'essai	46
6.3.1 Etat mécanique	46
6.3.2 Essais fonctionnels	47
6.3.3 Essais de performance	47
6.4 Reproductibilité des essais de vibrations aléatoires	47
6.4.1 Densité spectrale d'accélération (ASD)	47
6.4.2 Valeur quadratique moyenne (valeur efficace)	47
6.4.3 Fonction de densité de probabilité (PDF, <i>Probability density function</i>)	47
6.4.4 Durée	48
6.5 Tolérances de mesure	48
6.6 Conditions de reprise des essais	48
7 Mesures initiales et préconditionnement	48
8 Conditions d'essais fonctionnels de vibrations aléatoires	48
8.1 Sévérité d'essai et gamme de fréquences	48
8.2 Durée des essais fonctionnels de vibrations	49
8.3 Fonctionnement pendant l'essai	49
9 Essais d'endurance simulée à des niveaux de vibrations aléatoires augmentés	49
9.1 Sévérité d'essai et gamme de fréquences	49
9.2 Durée des essais de vibrations accélérés	50
10 Conditions d'essais de chocs	50
10.1 Forme d'impulsion et tolérance	50
10.2 Variations de vitesse	50
10.3 Montage	51
10.4 Taux de répétition	51
10.5 Sévérité des essais, forme et direction des impulsions	51
10.6 Nombre de chocs	51
10.7 Fonctionnement pendant l'essai	51
11 Transport et manutention	51
12 Mesures finales	51
13 Critères d'acceptation	52
14 Rapport	52

15 Attestation d'essai	52
16 Remise à disposition	53
Annexe A (informative) Commentaire à propos des mesures en service, des positions de mesure, des méthodes d'acquisition des données en service, du relevé des données en service et des méthodes utilisées pour obtenir des niveaux d'essais aléatoires à partir des données en service acquises	60
Annexe B (informative) Figure identifiant l'emplacement général du matériel sur les véhicules ferroviaires et la catégorie d'essai qui en résulte	67
Annexe C (informative) Exemple d'une attestation d'essai de type	68
Annexe D (informative) Guide pour le calcul des valeurs efficaces (RMS) à partir des valeurs ou des niveaux d'ASD	69
Figure 1 – Loi de Gauss	43
Figure 2 – Catégorie 1 – Classe A – Montage sur caisse – Spectre ASD	54
Figure 3 – Catégorie 1 – Classe B – Montage sur caisse – Spectre ASD	55
Figure 4 – Catégorie 2 – Montage sur bogie – Spectre ASD	56
Figure 5 – Catégorie 3 – Montage sur essieu – Spectre ASD	57
Figure 6 – Bandes de tolérances PDF cumulatives	58
Figure 7 – Forme d'impulsion et limites de tolérance pour impulsion demi-sinusoïdale	59
Figure A.1 – Positions de mesures normalisées utilisées pour les essieux, les bogies (châssis) et les caisses	60
Figure A.2 – Courbe typique de résistance à la fatigue	64
Figure B.1 – Emplacement général du matériel sur les véhicules	67
Figure D.1 – Spectre ASD	70
Tableau 1 – Sévérité d'essai et gamme de fréquences pour les essais fonctionnels de vibrations aléatoires	49
Tableau 2 – Sévérité d'essai et gamme de fréquences	50
Tableau 3 – Sévérité des essais, forme et direction des impulsions	51
Tableau A.1 – Relevé d'acquisition des données d'environnement des paramètres/conditions d'essai	61
Tableau A.2 – Relevé des niveaux d'accélération efficaces obtenus à partir du questionnaire	63
Tableau A.3 – Niveaux d'essai obtenus à partir des données en service en utilisant la méthode donnée à l'Article A.4	66

COMMISSION ÉLECTROTECHNIQUE INTERNATIONALE

APPLICATIONS FERROVIAIRES – MATÉRIEL ROULANT – ESSAIS DE CHOCS ET VIBRATIONS

AVANT-PROPOS

- 1) La Commission Electrotechnique Internationale (CEI) est une organisation mondiale de normalisation composée de l'ensemble des comités électrotechniques nationaux (Comités nationaux de la CEI). La CEI a pour objet de favoriser la coopération internationale pour toutes les questions de normalisation dans les domaines de l'électricité et de l'électronique. A cet effet, la CEI – entre autres activités – publie des Normes internationales, des Spécifications techniques, des Rapports techniques, des Spécifications accessibles au public (PAS) et des Guides (ci-après dénommés "Publication(s) de la CEI"). Leur élaboration est confiée à des comités d'études, aux travaux desquels tout Comité national intéressé par le sujet traité peut participer. Les organisations internationales, gouvernementales et non gouvernementales, en liaison avec la CEI, participent également aux travaux. La CEI collabore étroitement avec l'Organisation Internationale de Normalisation (ISO), selon des conditions fixées par accord entre les deux organisations.
- 2) Les décisions ou accords officiels de la CEI concernant les questions techniques représentent, dans la mesure du possible, un accord international sur les sujets étudiés, étant donné que les Comités nationaux de la CEI intéressés sont représentés dans chaque comité d'études.
- 3) Les Publications de la CEI se présentent sous la forme de recommandations internationales et sont agréées comme telles par les Comités nationaux de la CEI. Tous les efforts raisonnables sont entrepris afin que la CEI s'assure de l'exactitude du contenu technique de ses publications; la CEI ne peut pas être tenue responsable de l'éventuelle mauvaise utilisation ou interprétation qui en est faite par un quelconque utilisateur final.
- 4) Dans le but d'encourager l'uniformité internationale, les Comités nationaux de la CEI s'engagent, dans toute la mesure possible, à appliquer de façon transparente les Publications de la CEI dans leurs publications nationales et régionales. Toutes divergences entre toutes Publications de la CEI et toutes publications nationales ou régionales correspondantes doivent être indiquées en termes clairs dans ces dernières.
- 5) La CEI elle-même ne fournit aucune attestation de conformité. Des organismes de certification indépendants fournissent des services d'évaluation de conformité et, dans certains secteurs, accèdent aux marques de conformité de la CEI. La CEI n'est responsable d'aucun des services effectués par les organismes de certification indépendants.
- 6) Tous les utilisateurs doivent s'assurer qu'ils sont en possession de la dernière édition de cette publication.
- 7) Aucune responsabilité ne doit être imputée à la CEI, à ses administrateurs, employés, auxiliaires ou mandataires, y compris ses experts particuliers et les membres de ses comités d'études et des Comités nationaux de la CEI, pour tout préjudice causé en cas de dommages corporels et matériels, ou de tout autre dommage de quelque nature que ce soit, directe ou indirecte, ou pour supporter les coûts (y compris les frais de justice) et les dépenses découlant de la publication ou de l'utilisation de cette Publication de la CEI ou de toute autre Publication de la CEI, ou au crédit qui lui est accordé.
- 8) L'attention est attirée sur les références normatives citées dans cette publication. L'utilisation de publications référencées est obligatoire pour une application correcte de la présente publication.
- 9) L'attention est attirée sur le fait que certains des éléments de la présente Publication de la CEI peuvent faire l'objet de droits de propriété intellectuelle ou de droits analogues. La CEI ne saurait être tenue pour responsable de ne pas avoir identifié de tels droits de propriété et de ne pas avoir signalé leur existence.

La Norme internationale CEI 61373 a été établie par le comité d'études 9 de la CEI: Matériels et systèmes électriques ferroviaires.

Cette deuxième édition annule et remplace la première édition, parue en 1999, dont elle constitue une révision technique.

Les principaux changements techniques par rapport à l'édition précédente sont les suivants:

- changement de la méthode pour calculer le taux d'accélération qui doit être appliqué à la valeur fonctionnelle de la densité spectrale d'accélération (ASD) pour obtenir une valeur simulée d'ASD sur le long terme;
- ajout de la notion de certification partielle par rapport à la norme;
- suppression de l'Annexe B de la première édition compte tenu de la nouvelle méthode de calcul du taux d'accélération;

- ajout de recommandations pour le calcul de la valeur efficace fonctionnelle à partir des données de service, ou de la valeur efficace à partir des niveaux d'ASD des Figures 2 à 5.

Le texte de cette norme est issu des documents suivants:

FDIS	Rapport de vote
9/1386/FDIS	9/1397/RVD

Le rapport de vote indiqué dans le tableau ci-dessus donne toute information sur le vote ayant abouti à l'approbation de cette norme.

Le comité a décidé que le contenu de cette publication ne sera pas modifié avant la date de stabilité indiquée sur le site web de la CEI sous "<http://webstore.iec.ch>" dans les données relatives à la publication recherchée. A cette date, la publication sera

- reconduite,
- supprimée,
- remplacée par une édition révisée, ou
- amendée.

IMPORTANT – Le logo "colour inside" qui se trouve sur la page de couverture de cette publication indique qu'elle contient des couleurs qui sont considérées comme utiles à une bonne compréhension de son contenu. Les utilisateurs devraient, par conséquent, imprimer cette publication en utilisant une imprimante couleur.