


## PUBLICLY AVAILABLE SPECIFICATION



Reference number IEC/PAS 62323





## PUBLICLY AVAILABLE SPECIFICATION



Reference number IEC/PAS 62323

#### INTERNATIONAL ELECTROTECHNICAL COMMISSION

# DIMENSIONS OF HALF POT CORES MADE OF MAGNETIC OXIDES FOR INDUCTIVE PROXIMITY SWITCHES

#### **FOREWORD**

A PAS is a technical specification not fulfilling the requirements for a standard, but made available to the public.

IEC-PAS 62323 has been processed by IEC technical committee 51: Magnetic components and ferrite materials.

The text of this PAS is based on the following document:

This PAS was approved for publication by the P-members of the committee concerned as indicated in the following document:

| Draft PAS  | Report on voting |
|------------|------------------|
| 51/657/PAS | 51/674/RVD       |

Following publication of this PAS, the technical committee or subcommittee concerned will investigate the possibility of transforming the PAS into an International Standard.

- 1) The IEC (International Electrotechnical Commission) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of the IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, the IEC publishes International Standards. Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International governmental and non-governmental organizations liaising with the IEC also participate in this preparation. The IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of the LEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested National Committees.
- 3) The documents produced have the form of recommendations for international use and are published in the form of standards, technical specifications, technical reports or guides and they are accepted by the National Committees in that sense.
- 4) In order to promote international unification, IEC National Committees undertake to apply IEC International Standards transparently to the maximum extent possible in their national and regional standards. Any divergence between the IEC Standard and the corresponding national or regional standard shall be clearly indicated in the latter.
- 5) The IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with one of its standards.
- 6) Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. The IEC shall not be held responsible for identifying any or all such patent rights.

# DIMENSIONS OF HALF POT CORES MADE OF MAGNETIC OXIDES FOR INDUCTIVE PROXIMITY SWITCHES

#### 1 Scope

This PAS lays down the important dimensions for the mechanical interchangeability of a preferred half pot-core series of magnetic oxides, intended to be used in inductive proximity switches.

#### 2 Normative references

The following normative document contains provisions which, through references in this text, constitute provisions of this International Standard. For dated references subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of ISO and IEC maintain registers of currently valid International Standards.

IEC 60424-1:1999, Ferrite cores – Guide on the limit of surface irregularities – Part 1: General specification

3 Dimensions
3.1 Nomenclature of dimensions

B

B

B

Figure 1 - Nomenclature of dimensions

#### 3.2 Dimensions and tolerance

The main dimensions and tolerances shall be as given in table 1.

Table 1 - Dimensions and tolerances

Dimensions in millimetres

| Core type | Dimensions  |      | Α     | E    |       | F    |       | В    |       | D    |       |
|-----------|-------------|------|-------|------|-------|------|-------|------|-------|------|-------|
|           |             | Dim. | Tol.  |
| PS 3,3    | 3,3 x 1,3   | 3,35 | -0,15 | 2,5  | +0,1  | 1,20 | -0,1  | 1,3  | -0,2  | 0,85 | +0,2  |
| PS 5,6    | 5,6 x 1,7   | 5,6  | -0,25 | 4,5  | +0,15 | 2,5  | -0,1  | 1,7  | -0,2  | 1,1  | +0,2  |
| PS 7,35   | 7,35 x 3,6  | 7,35 | -0,25 | 5,8  | +0,2  | 3,0  | -0,15 | 3,6  | -0,2  | 2,8  | +0,2  |
| PS 9,0    | 9,0 x 3,5   | 9,0  | -0,4  | 7,3  | +0,3  | 3,9  | -0,25 | 3,5  | -0,2  | 2,6  | +0,2  |
| PS 11     | 11,3 x 3,3  | 11,3 | -0,4  | 9,0  | +0,4  | 4,7  | -0,2  | 3,3  | -0.1  | 2,2  | +0,15 |
| PS 14     | 14,3 x 4,25 | 14,3 | -0,5  | 11,6 | +0,4  | 6,0  | -0,2  | 4,25 | -0,15 | 2,8  | +0,2  |
| PS 25     | 24,8 x 8,9  | 24,8 | -1,0  | 20,5 | +0,8  | 11,3 | -0,5  | 8,9  | -0,2  | 5,9  | +0,3  |
| PS 30,5   | 30,5 x 10,2 | 30,5 | -1,0  | 25   | +0,8  | 13,5 | -0,4  | 10,2 | -0,3  | 7,0  | +0,35 |
| PS 35     | 35 x 10,8   | 35   | -1,0  | 29,4 | +0,8  | 15,7 | -0(5  | 10,8 | 10,35 | 7,2  | +0,4  |
| PS 47     | 47 x 14     | 47   | -1,3  | 39   | +1,1  | 20 / | -0,6  | 14   | -0,5  | 9,5  | +0,5  |
| PS 68     | 68 x 14,5   | 68   | -2,2  | 57,5 | +1,8  | 29,5 | 1,0   | 14,5 | -0,6  | 9,0  | +0,6  |

NOTE 1 The core may have up to two slots in order to realise the wire connection feed through holes.

NOTE 2 A centre hole (H) is allowable.

NOTE 3 Chamfers are allowable as long as they do not limit the winding space.

### 4 Requirements

In order to avoid damages of the coils and their connection wires, the core shall be delivered without burrs. Flashes according to 3 3 of JEC 60424-1 shall not be present either on the winding area limiting surfaces including edges or on the wire connection feed through holes.

### 5 Marking

A manufacturer specific marking is mandatory from PS 7,35 and larger, preferably on the bottom of the core.

# Annex A (informative)

### **Bibliography**

The following literature gives additional information.

IEC 60133:2000, Dimensions of pot-cores made of magnetic oxides and associated parts

IEC 60424-2 :1997, Ferrite cores - Guide on the limit of surface irregularities - Part 2: RM-cores

IEC 61332:1995, Soft ferrite material classification

IEC 60367-1:1982, Cores for inductors and transformers for telecommunications — Part 1: Measuring methods

IEC 60367-2 :1974, Cores for inductors and transformers for telecommunications – Part 2: Guides for the drafting of performance specifications

IEC 62044: Cores made of soft magnetic materials - Measuring methods

Part 1: Generic specification

Part 21): Measurement of magnetic properties at low excitation levels

Part 3 : Measurement of magnetic properties at high excitation levels

<sup>1)</sup> To be published.

