

INTERNATIONAL  
STANDARD

ISO  
15685

Second edition  
2012-07-15

---

---

**Soil quality — Determination of potential  
nitrification and inhibition of nitrification —  
Rapid test by ammonium oxidation**

*Qualité du sol — Détermination de la nitrification potentielle et inhibition  
de la nitrification — Essai rapide par oxydation de l'ammonium*

STANDARDSISO.COM : Click to view the full PDF of ISO 15685:2012



Reference number  
ISO 15685:2012(E)

© ISO 2012

STANDARDSISO.COM : Click to view the full PDF of ISO 15685:2012



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2012

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

## Contents

	Page
<b>Foreword</b>	iv
1 <b>Scope</b>	1
2 <b>Normative references</b>	1
3 <b>Terms and definitions</b>	1
4 <b>Principle</b>	2
5 <b>Reagents</b>	2
6 <b>Apparatus</b>	3
7 <b>Sampling, storage and characterization of samples</b>	3
8 <b>Procedure</b>	4
8.1 <b>Testing soils</b>	4
8.2 <b>Testing the effect of chemicals</b>	4
8.3 <b>Testing polluted soils</b>	4
8.4 <b>Testing water extracts of biosolids</b>	5
9 <b>Calculations</b>	5
10 <b>Test report</b>	5
<b>Annex A (informative) Results of a laboratory ring test</b>	7
<b>Annex B (informative) Micro-scale measurement of potential nitrification rates</b>	9
<b>Bibliography</b>	11

STANDARDSISO.COM : Click to view the full PDF of ISO 15685:2012

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 15685 was prepared by Technical Committee ISO/TC 190, *Soil quality*, Subcommittee SC 4, *Biological methods*.

This second edition cancels and replaces the first edition (ISO 15685:2004), which has been technically revised.

# Soil quality — Determination of potential nitrification and inhibition of nitrification — Rapid test by ammonium oxidation

## 1 Scope

This International Standard specifies a rapid method for the determination of the potential rate of ammonium oxidation and inhibition of nitrification in soils. This method is suitable for all soils containing a population of nitrifying microorganisms. It can be used as a rapid screening test for monitoring soil quality and quality of wastes, and is suitable for testing the effects of cultivation methods, chemical substances [except volatiles, i.e.  $H > 1$  (Henry's constant)], extracts of biosolids and pollution in soils.

## 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 10381-6, *Soil quality — Sampling — Part 6: Guidance on the collection, handling and storage of soil under aerobic conditions for the assessment of microbiological processes, biomass and diversity in the laboratory*

ISO 10390, *Soil quality — Determination of pH*

ISO 10694, *Soil quality — Determination of organic and total carbon after dry combustion (elementary analysis)*

ISO 11260, *Soil quality — Determination of effective cation exchange capacity and base saturation level using barium chloride solution*

ISO 11261, *Soil quality — Determination of total nitrogen — Modified Kjeldahl method*

ISO 11277, *Soil quality — Determination of particle size distribution in mineral soil material — Method by sieving and sedimentation*

ISO 11465, *Soil quality — Determination of dry matter and water content on a mass basis — Gravimetric method*

ISO 14238, *Soil quality — Biological methods — Determination of nitrogen mineralization and nitrification in soils and the influence of chemicals on these processes*

ISO 14256-2, *Soil quality — Determination of nitrate, nitrite and ammonium in field-moist soils by extraction with potassium chloride solution — Part 2: Automated method with segmented flow analysis*

EN 14735, *Characterization of waste — Preparation of waste samples for ecotoxicity tests*

## 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

### 3.1

#### inhibitory dose

##### ID

amount of a chemical added to soil that effectively inhibits biological activity by a stated percentage after a given time, in comparison with an untreated control

NOTE It is expressed as a percentage. For example, ID25 and ID50 indicate a 25 % and 50 % inhibition of biological activity, respectively.

**3.2****biosolids**

organic products used in agriculture, which include sewage sludge, compost, manure and some industrial wastes

## 4 Principle

Ammonium oxidation, the first step in autotrophic nitrification in soil, is used to assess the potential activity of microbial nitrifying populations. Autotrophic ammonium-oxidizing bacteria are exposed to ammonium sulfate in a soil slurry buffered at pH 7,2. Oxidation of the nitrite performed by nitrite-oxidizing bacteria in the slurry is inhibited by the addition of sodium chlorate. The subsequent accumulation of nitrite is measured over a 6 h incubation period, and is taken as an estimate of the potential activity of ammonium-oxidizing bacteria. As the generation time of ammonia-oxidizing bacteria is long (> 10 h), the method provides a measure of the potential activity of the nitrifying population at the time of sampling. It does not measure growth of the nitrifying population.

Chemical test substances and extracts of biosolids can be tested by adding them to the slurry at various concentrations. The test can be used for comparison of different soils (e.g. polluted and reference soils). Effects of polluted soils, waste samples and other solid materials on nitrification can be evaluated by measuring the method on mixtures of these samples with a reference soil.

Substances known to be active at pH < 7,2 should be added in due time before starting the test to allow substances to exhibit their effects on nitrifying bacteria.

## 5 Reagents

**5.1 Distilled water.**

**5.2 Potassium dihydrogenphosphate**,  $c(\text{KH}_2\text{PO}_4 = 0,2 \text{ mol/l})$ .

**5.3 Dipotassium hydrogenphosphate**,  $c(\text{K}_2\text{HPO}_4 = 0,2 \text{ mol/l})$ .

**5.4 Sodium chlorate**,  $c(\text{NaClO}_3 = 0,5 \text{ mol/l})$ .

**5.5 Diammonium sulfate**,  $(\text{NH}_4)_2\text{SO}_4$ .

**5.6 Sodium hydrogencarbonate**,  $c(\text{NaHCO}_3 = 5 \text{ mmol/l})$ .

**5.7 Potassium chloride**,  $c(\text{KCl} = 4 \text{ mol/l})$ .

**5.8 Stock solution A.**

Prepare stock solution A as follows.

Potassium dihydrogenphosphate,  $\text{KH}_2\text{PO}_4$  (5.2) 28 ml

Dipotassium hydrogenphosphate,  $\text{K}_2\text{HPO}_4$  (5.3) 72 ml

Distilled water (5.1) 100 ml

**5.9 Test medium.**

Prepare the test medium as follows.

Stock solution A (5.8) 10 ml

Sodium chlorate,  $\text{NaClO}_3$  (5.4) 10 ml to 30 ml

Diammonium sulfate,  $(\text{NH}_4)_2\text{SO}_4$  (5.5) 0,198 g

Dilute to 1 000 ml with distilled water (5.1).

The test medium contains 1 mmol/l of potassium phosphate buffer, 5 mmol/l to 15 mmol/l of sodium chlorate and 1,5 mmol/l of diammonium sulfate, and has a pH of approximately 7,2.

The sodium chlorate concentration selected within the range given should be sufficient for effective inhibition of biological nitrate formation, while not having negative effects on ammonium oxidation. If necessary, test the influence of the sodium chlorate concentration.

Test chemicals to be added to the test medium shall be dissolved in the phosphate buffer described and added before diluting to 1 l. For test chemicals with low water solubility, prepare solutions by mechanical dispersion or by using vehicles such as organic solvents, emulsifiers or dispersants of low toxicity to ammonium-oxidizing bacteria. If any vehicle is used to add a test chemical to the slurry or a soil, additional control shall be performed to assess possible effects of this vehicle on ammonium oxidation.

Add extracts of biosolids, when tested, separately to the test medium before dilution to 1 l.

NOTE When a carbon source is needed, e.g. when testing biosolids with high nitrate levels, add 10 ml of NaHCO<sub>3</sub> (5.6) to the test medium before diluting to 1 l.

## 6 Apparatus

### 6.1 Ordinary laboratory equipment.

### 6.2 Orbital shaking incubator, thermostatically controlled.

## 7 Sampling, storage and characterization of samples

Guidance on sampling, sample processing and storage is given in ISO 10381-6. For the testing of chemicals or biosolids, or for mixing tests with polluted soils, experimental soil with an ammonium-oxidizing activity of between 200 ng N/g and 800 ng N/g of dry mass of soil/h, determined from a preliminary experiment, should be chosen. When testing chemicals, the soil should have a low adsorption capacity (e.g. sandy soils low in C<sub>org</sub> < 1 %); on the other hand, the soil should have a pH between 5,5 and 7,5.

Soil samples can usually be stored in a refrigerator at approximately 4 °C for periods of up to three months prior to use (ISO 10381-6). Some soils can only be kept in a refrigerator for up to two weeks. Storage of soil samples in a freezer (–20 °C) is not generally recommended.

It has been shown for a number of soils from temperate climates that storage at –20 °C for up to 12 months does not inhibit ammonium oxidation activity (Reference [4]). Where such information is available for a particular soil, storage under such conditions is permissible.

Measurement of the following variables is recommended for characterization of the soil:

- particle size distribution (ISO 11277);
- water content (ISO 11465);
- water-holding capacity (ISO 14238);
- pH (ISO 10390);
- effective cation exchange capacity (ISO 11260);
- organic matter content (ISO 10694);
- total nitrogen content (ISO 11261).

## 8 Procedure

### 8.1 Testing soils

#### 8.1.1 General

The test design should include at least three replicates of approximately 25 g of moist soil. The water content of soil for the calculation of dry mass is determined gravimetrically according to ISO 11465.

#### 8.1.2 Initial incubation

Mix soil samples or waste materials with test medium (5.9) to form slurries. The volume of test medium should be adjusted to give a precise total liquid volume, e.g. 100 ml. Calculate the volume of medium to be added by subtracting the volume of water in the initial soil or waste sample from the desired liquid volume, e.g. 100 ml. Incubate the slurries in 250 ml flasks, placed upright on the orbital shaking incubator (6.2), thermostatically controlled at  $(25 \pm 2)^\circ\text{C}$ . Rotation should be sufficient to keep solids suspended (175 r/min).

A liquid volume greater than 100 ml is required in the slurry if the water-holding capacity of the soil is  $> 200\%$  (organic soils).

#### 8.1.3 Sampling of soil slurry

Take samples (2 ml) of the soil slurry after 2 h and 6 h of incubation, provided that ammonium oxidation is known to be linear over this period. The soil slurry should be well shaken at sampling times to ensure that the ratio of solution to soil is constant during the test. Dispense samples into test tubes and add 2 ml of KCl (5.7) to stop the ammonium oxidation. Then centrifuge the samples at, for example, 3 000g for 2 min, or filter. Filter paper should be of high filtration speed, while its chemical purity may be less than the highest grade. Determine nitrite by a suitable method of chemical analysis (see ISO 14256-2). At this stage, the solutions can be stored in a refrigerator ( $4^\circ\text{C}$  to  $8^\circ\text{C}$ ) but analysis should be carried out within 24 h.

If necessary, check the linearity of the ammonium oxidation over time by sampling soil slurry a number of times during the 6 h of incubation. This is likely to be necessary if laboratories are not familiar with the soil types being used in the test. Some cases of non-linearity can be corrected by ensuring aerobic conditions or supplying a carbon source.

### 8.2 Testing the effect of chemicals

Determine ammonium oxidation according to the procedure for soils by adding test chemicals to the test medium (5.9) at different concentrations. Include controls with no added test chemical in the test design as a reference. The number of replicates of the control should be twice the number of replicates chosen for each concentration of test chemical.

Conduct a preliminary range-finding test to select the concentrations of test chemical. In the main test, arrange at least five different concentrations in a geometric progression. The lowest concentration tested should have no effect on ammonium oxidation and the highest should inhibit by 50 % to 100 %.

When a vehicle for dissolution of a chemical is used, it should not exceed 100 mg/l in the test medium. Its effect on ammonium oxidation should be tested by having additional controls containing the vehicle at the highest concentration used in the test.

NOTE Volatile test substances require special arrangements which are not within the scope of this International Standard.

### 8.3 Testing polluted soils

The most straightforward method is to compare the polluted soil with an unpolluted reference soil with comparable soil properties, or to make gradient studies on soil samples taken at various levels of pollution. Take a sufficient quantity of soil in order to prepare at least four replicates.

In the absence of a suitable unpolluted soil for reference, or in cases of low potential nitrification activity, the following test procedure is recommended. Pre-incubate the polluted soil and an unpolluted soil of known nitrification activity at 200 ng N/g dm of soil/h to 800 ng N/g dm of soil/h at a water content of 40 % to 60 % of water-holding capacity or -0,01 MPa to -0,03 MPa suction pressure for two days at 20 °C in darkness. Mix moist amounts of the two soils comparable to 75 g of dry mass in a 1:1 ratio on a dry-mass basis. Store the mixture, the polluted soil and the control soil for 24 h at 20 °C in darkness. Measure the potential ammonium oxidation as described in 8.1 using four replicates of the mixture and of each soil.

#### 8.4 Testing water extracts of biosolids

The effect on soil nitrification by extracts of biosolids, e.g. sewage sludge, can be tested. Prepare water extracts by 24 h extraction with demineralized water at a ratio of 1:10 [g of biosolid (dry mass):ml of water] and pH 7,5 (see EN 14735). Separate the aqueous phase from the particles by centrifugation, e.g. at 1 300g for 1 h. Test the effect of the extract on soil in a concentration series, including controls with no extract. Follow the test procedure given in 8.1, adding the extract of biosolid just before the addition of test medium. Include extract samples without soil in the test design for subtraction of ammonium oxidation by nitrifying bacteria in the extracts.

### 9 Calculations

Calculate the rate of ammonium oxidation (ng NO<sub>2</sub>-N/g of dry mass of soil/h) from the difference between NO<sub>2</sub>-N concentrations at different measuring times.

Calculate the inhibition of ammonium oxidation activity by the test chemical or extract of biosolid as a change in the activity in reference soil, expressed as a percentage.

In mixtures of polluted and unpolluted soils, the polluted soil is considered toxic if the mixture shows ammonium oxidation significantly lower than 90 % of the mean activity of the two soils kept separate. Using four replicates, this is calculated using Equation (1):

$$\bar{A}_m + s_m < 0,9 \times \frac{(\bar{A}_c + \bar{A}_p)}{2} \quad (1)$$

where

$\bar{A}_m$  is the mean ammonium oxidation activity in the soil mixture;

$s_m$  is the standard deviation of ammonium oxidation activity in the soil mixture;

$\bar{A}_c$  is the mean ammonium oxidation activity in the control soil;

$\bar{A}_p$  is the mean ammonium oxidation activity in the polluted soil.

### 10 Test report

The test report shall contain the following information:

- a reference to this International Standard;
- soil characteristics;
- rate of ammonium oxidation (ng NO<sub>2</sub>-N/g of dry mass of soil/h), individual values, mean values and standard deviations for each treatment and soil;
- test of reaction linearity:
  - if reaction linearity was tested at three sampling times or more, a plot of nitrite-N concentration versus time is reported;

- e) tests with added chemicals:
  - graphical representation of inhibition of ammonium oxidation versus concentration of the tested chemical; inhibitory dose values ID25 and ID50 indicated in the diagram (see 3.1);
- f) test report for polluted soil in soil mixtures:
  - qualitative classification of polluted soils as toxic or non-toxic (see Annex A);
- g) test report for extracts of biosolids:
  - graphical representation of the concentration-effect relationship of added water extracts from biosolids, including an estimation of inhibitory dose values ID25 and ID50.

STANDARDSISO.COM : Click to view the full PDF of ISO 15685:2012

## Annex A

### (informative)

### Results of a laboratory ring test

A laboratory ring test using four contaminated soils and a reference soil (see Table A.1) was carried out in Germany. In addition to the determination of ammonium oxidation rates (see Table A.2), a toxicity test using mixtures (1:1) of the reference soil and the polluted soils was performed according to the procedure described in 8.3 (see Table A.3). Extreme values were eliminated according to DIN 38402-42 [7].

In agreement with Clause 7, only the reference soil and soil 1 were in the recommended range of 200 ng N/g to 800 ng N/g of dry mass of soil/h. Within this ring test, additional contaminated soils were tested which had a very low level of ammonium oxidation activity. The high coefficients of variation ( $C_V$ ) for contaminated soils can be attributed to the fact that the values approached zero. Therefore, these numbers do not affect the outcome of the ring test (see Table A.2). However, qualitative toxicity assessment using the soil mixing procedure of 8.3 was applied with good agreement between laboratories for all soils, including low-activity soil (Table A.3).

**Table A.1 — Chemical and physical properties of the soils and their contamination**

Parameter	Reference soil	Soil 1	Soil 2	Soil 3	Soil 4
Textural class	silty sand	loam	sand	sand	sand
WHC <sub>max</sub> , ml/kg	290,0	511,8	347,7	241,8	268,5
pH	6,6	7,3	7,3	7,5	5,6
C <sub>org</sub> , %	2,1	4,7	8,5	5,9	1,7
N, %	0,16	0,38	0,27	0,20	0,16
ΣNitrotoluene, mg/kg	n.d.	336,3	n.d.	n.d.	n.d.
PAH, mg/kg	n.d.	77,0	60	21	2 268
Mineral oil, mg/kg	n.d.	< 50,0	43 660,1	8798,9	< 50
As, mg/kg	n.d.	5,4	3,6	12,1	< 3
Cd, mg/kg	n.d.	6,4	29,6	9,3	< 3
Cr, mg/kg	n.d.	65,9	2 005,1	320,3	94,9
Cu, mg/kg	n.d.	104,4	10 921,3	367,8	10,0
Ni, mg/kg	n.d.	29,2	5 894,2	578,5	6,5
Pb, mg/kg	n.d.	820,8	1 082,2	547,5	10,3
Zn, mg/kg	n.d.	764,7	5 065,3	577,6	26,6
NOTE	n.d.: not determined.				
WHC: water-holding capacity; PAH: polycyclic aromatic hydrocarbons					

**Table A.2 — Ammonium oxidation rates**

Soils	Reference	Soil 1	Soil 2	Soil 3	Soil 4
Mean value, ng NO <sub>2</sub> -N/g of dry mass of soil/h	540	350	80	10	10
Standard deviation	93	138	122	14	14
$C_V$ , %	17,2	39,5	153,3	142,6	135,7
Number of participating laboratories	23	16	15	16	16
Number of laboratories considered	22	16	14	15	12

**Table A.3 — Assessment of toxicity of contaminated soils using soil mixtures with the reference soil according to 8.3** [toxicity criteria: see Clause 9, Equation (1)]

Laboratory	Soil 1	Soil 2	Soil 3	Soil 4
6	/	/	/	/
19	-	+	+	-
23	+	+	+	+
25	-	+	+	+
26	-	+	+	+
28	-	/	+	+
30	-	+	+	-
35	-	+	+	-
41	-	+	+	+
45	/	/	/	/
46	-	+	+	
49	-	+	+	+
51	-	+	+	+
55	-	+	+	-
57	-	+	+	+
58	-	+	+	+
60	+	+	+	+
Toxic (%)	13,3	100	100	73,3

NOTE    + = toxic;  
       - = not toxic;  
       / = not determined.