INTERNATIONAL STANDARD

ISO 23512

First edition 2021-03

Plastics — Joining of thermoplastic moulded components — Specification of variables for thermal joining processes

Plastiques — Assemblage de composants thermoplastiques moulés — Spécification de variables pour les procédés d'assemblage thermique variables pour les procédés



STANDARDS & O.COM. Click to view the full Poly.



COPYRIGHT PROTECTED DOCUMENT

© ISO 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

Cont	ents	Page
Forewo	rd	iv
Introdi	ction	v
	cope	
	•	
	lormative references	
	erms and definitions	
	echnical content of thermal joining process specification (TJPS)	
	.1 General	3 2
	Related to the joining organization Related to the sub-component(s) Common to all joining processes	3 3
	.4 Common to all joining processes	3
	.5 Specific to a joining process	4
	.5 Specific to a joining process 4.5.1 Ultrasonic welding/staking/spot welding	4
	4.5.2 Infrared welding	4
	4.5.3 Hot gas convection welding	5
	4.5.5 Orbital vibration welding	5
	4.5.6 Spin welding 4.5.7 Laser welding	5
	4.5.7 Laser welding 4.5.8 Hot plate welding	
	4.5.7 Laser weiding 4.5.8 Hot plate welding 4.5.9 Heat staking – hot air 4.5.10 Heat staking – electrical 4.5.11 Heat staking – infrared	
	4.5.10 Heat staking – flot all	7 7
	4.5.11 Heat staking – infrared	7
Annov	(informative) Template for TJPS: Ultrasonic welding/staking/spot welding	
	(informative) Template for TJPS: Infrared welding8	
	(informative) Template for TJPS: Hot gas convection welding	
	(informative) Template for FJPS: Linear vibration welding	
	(informative) Template for TJPS: Orbital vibration welding	
	(informative) Template for TJPS: Spin welding	
Annex	(informative) Template for TJPS: Laser welding	21
Annex	I (informative) Template for TJPS: Hot plate welding	23
Annex	(informative) Template for TJPS: Heat staking - hot air	25
Annex	(informative) Template for TJPS: Heat staking - electrical	27
	(informative) Template for TJPS: Heat staking - infrared	
_	(informative) Worked example for TJPS: Hot plate welding	
	(informative) Worked example for TJPS: Heat staking - electrical	
	aphy	

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee 150/TC 61, *Plastics*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

iv

Introduction

This document has been developed to help organizations better understand and implement controls with thermal joining processes through the use of thermal joining process specifications.

STANDARDS 60.COM. Click to view the full POF of 150 235 12:2021

STANDARDS ISO COM. Click to view the full PDF of ISO 235 12:2021

Plastics — Joining of thermoplastic moulded components — Specification of variables for thermal joining processes

1 Scope

This document specifies the minimum essential variables in order to produce a component of the Meta view the full PDF of 150 235 12:2021 required consistency and quality for the following thermal joining processes:

- ultrasonic welding/staking/spot welding;
- infrared welding;
- hot gas convection welding;
- linear vibration welding;
- orbital vibration welding;
- spin welding;
- laser welding:
- hot plate welding;
- heat staking: hot air;
- heat staking: electrical; and
- heat staking: infrared (IR).

This document defines the thermal joining process specification (TJPS) for each of the thermal joining processes listed above, to ensure that all the essential variables are properly considered, including the qualified range of each variable, in order to establish and maintain component quality at an acceptable level.

Standards on joining of plastic pipes, fittings, valves and/or auxiliary equipment, and the assessment of the properties of the resulting joints are developed and maintained by ISO/TC 138.

Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 472, *Plastics* — *Vocabulary*

Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 472 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at https://www.iso.org/obp
- IEC Electropedia: available at http://www.electropedia.org/

3.1

dimensional report

full measurement report on product before welding including flatness at weld joint

3.2

essential variable

joining condition that influences the quality of the joint and requires qualification

3.3

joining organization

organization responsible for the serial production joining and maintenance of quality

3.4

joining procedure

specified course of action to be followed in making a joint, including the *joining process(es)* (3.5), reference to materials, preparation, pre-heating (if necessary), control of process parameters and necessary equipment to be used

3.5

joining process

method of softening or melting to obtain a permanent joint (3.7)

3.6

joining process qualification record $% \left(\mathbf{r}\right) =\left(\mathbf{r}\right) \left(\mathbf{r}\right)$

JPQR

record comprising all data of mechanical test results for the specified range of each *essential variable* (3.2) needed for qualification of a TJPS, used by the *joining organization* (3.3) as part of the sign-off documentation

3.7

joint

junction of two sub-components

3.8

moisture content

amount of moisture content in parent material at the time of welding (3.12)

3.9

process report

document confirming that the sub-component has been manufactured using the correct moulding process parameters, conditions, material grade, masterbatch reference, masterbatch percentage, and regrind percentage

3.10

thermal joining process specification

TJPS

document that has been qualified and provides the required variables of the *joining procedure* (3.4) to ensure repeatability during production

3.11

visual examination acceptance criteria document

document specifying imperfections on sub-components that affect the functionality of the joint, such as weld lines, burn marks, surface contamination

3.12

welding

process of uniting softened surfaces of materials, generally with the aid of heat

3.13

work instruction

simplified TJPS, suitable for joining process (3.5) owner

4 Technical content of thermal joining process specification (TJPS)

4.1 General

A TJPS shall provide the minimum information specified in 4.2 to 4.5 required to make a joint of acceptable quality, as part of the component manufacturing quality agreement between the joining organization and the customer.

TJPSs cover a certain range for each essential variable. The range of each essential variable shall be qualified using a JPQR, and the procedure for measuring each variable shall conform to agreed specifications.

When completing the TJPS the technical support/manual/documentation of the pining process equipment manufacturer or service supplier may be consulted.

NOTE 1 Example templates of TJPSs are given in <u>Annex A</u> to <u>Annex K</u>. Worked example TJPSs for hot plate welding and heat staking: electrical are given in <u>Annex L</u> and <u>Annex M</u>, respectively.

NOTE 2 A work instruction can be prepared for each specific, applicable TIPS as part of detailed production planning.

4.2 Related to the joining organization

- a) identification of the joining organization;
- b) TJPS reference number/revision;
- c) signature of the person responsible for approval, appointed by the joining organization.

NOTE The responsibilities, knowledge, skills and competence for the person responsible for approval are set out in PD CEN/TR 16862^[1].

4.3 Related to the sub-component(s)

- a) sub-component material:
 - material supplier name;
 - 2) designation of the material(s) and reference standard(s), if any, or an alternative identification if a reference standard does not exist;
 - 3) moisture content;
 - 4) regrind percentage;
 - 5) masterbatch reference and masterbatch percentage;
- b) dimensional report;
- c) process report;
- d) customer component/part number;
- e) supplier component/part number;
- f) visual examination acceptance criteria document number.

4.4 Common to all joining processes

- a) joint preparation;
- b) ambient temperature;

- sub-component temperature; c)
- joining process qualification record (JPQR).

4.5 Specific to a joining process

Ultrasonic welding/staking/spot welding 4.5.1

- joining process(es): welding, staking or spot welding; a)
- machine type (fixed or handheld); b)
- c)
- d)
- e)
- f)
- g)
- h)
- i)
- j)
- k)
- 1)
- m)
- n)

A template for the TJPS for ultrasonic welding/staking/spot welding is given in Annex A. NOTE

Infrared welding 4.5.2

- a) emitter condition;
- distance of sub-components from IR source; b)
- pre-heat/soak temperature (or power); c)
- pre-heat/soak time; d)
- full heat temperature/power; e)
- full heat time; f)
- removal of heating to sub-component contact time/changeover time; g)
- welding force; h)
- meltdown/collapse/weld displacement; i)
- j) cooling time.

A template for the TJPS for infrared welding is given in Annex B. NOTE

4.5.3 Hot gas convection welding

- a) gas flow rate;
- b) gas temperature;
- c) gas feed type;
- d) distance between sub-components and tool;
- heating time; e)
- f) removal of heating to sub-component contact time/changeover time;
- welding force; g)
- meltdown/collapse/weld displacement; h)
- cooling time. i)

NOTE

4.5.4 Linear vibration welding

- frequency; a)
- amplitude/amplitude profile; b)
- IR pre-heat time (if applicable);
- d) IR pre-heat power (if applicable);
- IR pre-heat changeover time (if applicable) e)
- welding force/force profile; f)
- meltdown/collapse/weld displacement;
- welding time; h)
- hold/cooling time. i)

NOTE A template for the TJPS for linear vibration welding is given in Annex D.

4.5.5 Orbital vibration welding

- frequency; a)
- b) amplitude/amplitude profile;
- welding force/force profile; c)
- meltdown/collapse/weld displacement; d)
- welding time; e)
- hold/cooling time.

NOTE A template for the TJPS for orbital vibration welding is given in Annex E.

Spin welding 4.5.6

machine type (servo-drive/inertia);

- b) head mass (inertia machines only);
- c) run-up time (inertia machines only);
- d) rotational speed;
- e) down speed;
- f) welding force/force profile;
- g) welding time;
- h) number of rotations (if applicable);
- i) meltdown/collapse/weld displacement;
- j) hold/cooling time;
- k) final angular position (if applicable).

NOTE A template for the TJPS for spin welding is given in Annex F.

4.5.7 Laser welding

- a) wavelength;
- b) laser power;
- c) peak power (pulse lasers only);
- d) pulse energy (pulse lasers only);
- e) pulse duration and repetition rate (pulse lasers only);
- f) beam delivery (contour);
- g) focal length of focusing lens;
- h) beam energy profile/dimensions;
- i) power density;
- j) laser transmission of lower sub-component;
- k) laser transmission of upper sub-component;
- l) laser absorber type (if applicable);
- m) welding/clamping force;
- n) scan speed (if applicable);
- o) number of passes (if applicable);
- p) weld time (if applicable);
- q) meltdown/collapse/weld displacement;
- r) temperature close/loop (if applicable);
- s) power mapping/zoning (if applicable);
- t) hold/cooling time.

NOTE A template for the TJPS for laser welding is given in <u>Annex G</u>.

en in Annex F.

Jewithe full PDF of 150 23512:202

Jewithe full PDF of 150 23512:202

Jewithe full PDF of 150 23512:202

4.5.8 Hot plate welding

- plate temperature;
- b) hot plate surface coating (if applicable);
- c) melting force;
- d) heating time;
- e) meltdown/collapse/displacement;
- f) removal of heating to part contact time/changeover time;
- g) welding force;
- h) weld collapse/displacement;
- hold/cooling time.

NOTE A template for the TJPS for hot plate welding is given in Annex H.

Heat staking - hot air 4.5.9

- hot air temperature; a)
- b) airflow;
- distance of stake pin from end of nozzle;
- d) heating time;
- e) changeover time;
- cold stake tool/platen force; f)
- g) cold stake tool contact time;
- h) final cold tool position/dead stop (if applicable).

A template for the TJPS for heat staking - hot air is given in Annex I. NOTE

4.5.10 Heat staking electrical

- heated tool temperature/temperature profile;
- b) heating time (if no temperature profile);
- c) tool/platen force;
- d) cooling time (if no temperature profile);
- release temperature (if no temperature profile); e)
- final tool position/dead stop (if applicable).

NOTE A template for the TJPS for heat staking - electrical is given in Annex J.

4.5.11 Heat staking - infrared

- IR power; a)
- b) distance of stake pin from heat source;

- c) heating time;
- d) cold stake tool/platen force;
- e) cold stake tool contact time.

NOTE A template for the TJPS for heat staking - infrared is given in Annex K.

STANDARDS 60.COM. Click to view the full POF of 150 235 12:2021

Annex A

(informative)

Template for TJPS: Ultrasonic welding/staking/spot welding

Thermal joining process specification (TJPS): Ultrasonic welding/staking/spot welding					
Joining organization:	TJPS reference number/revision:				
Component name:	2				
Customer component/ part number	Supplier component/ part number				
JPQR number:					
Sub-component A*:	Sub-component BC				

Sub-component A*:		Sub-component BC		
Material type/designation:		Material type/designation:		
Material supplier name		Material supplier name		
Material grade		Material grade		
Masterbatch reference		Masterbatch reference		
Masterbatch percentage		Masterbatch percentage		
Regrind (%)		Regrind (%)		
Moisture content range (%)	:(0)	Moisture content range (%)		
Dimensional report number	"04,	Dimensional report number		
Process report number	at it	Process report number		
Visual examination acceptance criteria document number	Clic	Visual examination acceptance criteria document number		

^{*} Sub-component A is the part in initial contact with the sonotrode/horn

Machine type (fixed/handheld):		
Frequency (kHz):		
Power rating (kW):		
Joining parameters	V	Value/tolerance or range
Ambient temperature (°C)		2
Sub-component temperature (°C)		0.12
Tool temperature (°C)		5
Tool face amplitude (µm) / amplitude profile		၅ကိ
Down speed (mm/s) (not handheld)		60
Trigger force (N) (if applicable) (not handheld)		, \S
Pre-trigger / touch (yes/no) (not handheld)		40
Pre-trigger amplitude (µm) (if applicable) (not handhe	eld)	ODY
Joining force (N) / force profile (not handheld)		
Meltdown / collapse / weld displacement (mm) (not h	andheld)	X *
Joining or welding time (s)	the	
Hold / cooling time (s)	No.	
Weld energy (J)	116	
<u> </u>		
Compiled by:	gnature:	
Da Da	ate:	
Approved by: Signature:		
Da	ate:	
oint design		
Provide the figure(s) of your joint design here.		
Amplitude profile diagram (if applicable)		

Provide diagram, it applicable.

Provide diagram, if applicable.

Force profile diagram (if applicable)

Annex B

(informative)

Template for TJPS: Infrared welding

Thermal joining process specification (TJPS): Infrared welding

Joining organization:		TJPS reference number/revision:			
Component name:			N.		
Customer component/ part number		Supplier con part number	component/ ber		
JPQR number:			000)		
Sub-component A:		Sub-compo			
Material type/designation:		Material type/designation:			
Material supplier name		Material sup	plier name		
Material grade		Material gra	de		
Masterbatch reference		Masterbatch	n reference		
Masterbatch percentage		Masterbatch	percentage		
Regrind (%)		Regrind (%)			
Moisture content range (%)	:(0)	Moisture co	ntent range (%)		
Dimensional report number	~0	Dimensional	l report number		
Process report number	4	Process repo	ort number		
Visual examination acceptance criteria document number	Jilo.	Visual examination acceptance criteria document number			
er reer la document namber		criteria doct			
Machine characteristics					
Machine identification:					
Emitter type:					
Joining parameters			Value/tolerance or	range	
Ambient temperature (°C)					
Sub-component temperature (°C)					
Emittercondition					
Distance of sub-components from IR					
Pre-heat/soak temperature (°C) / pov					
Pre-heat/soak time (s)					
Full heat temperature (°C) / power (%					
Full heat time (s)					
Removal of heating to sub-component ver time (s)					
Welding force (N)					
Meltdown / collapse / weld displacen					
Cooling time (s)					

Compiled by:	Signature:
	Date:
Approved by:	Signature:
	Date:

Joint design

Provide the figure(s) of your joint design here.

STANDARDS 60 COM. Click to view the full POF of 150 235 12:2021

Annex C

(informative)

Template for TJPS: Hot gas convection welding

Thermal joining process specification (TJPS): Hot gas convection welding					
Joining organization:	TJPS reference number/revision:				
Component name:		2			
		Supplier component/		3.7	
part number		part number		V.	
JPQR number:)	
Cook assume an eart A		Ch			
Sub-component A:		Sub-compo			
Material type/designation:		+	e/designation:		
Material supplier name		Material sup	11		
Material grade		Material gra			
Masterbatch reference		Masterbatch			
Masterbatch percentage		Masterbatch			
Regrind (%)		Regrind (%)			
Moisture content range (%)		+	ntent range (%)		
Dimensional report number	· ×0	+	l report number		
Process report number	- C+	Process report number			
			ination acceptar	nce	
criteria document number		criteria doci	ument number		
Machine characteristics					
Machine identification:					
Joining parameters			Value/toleran	ce or range	
Ambient temperature (°C)					
Sub-component temperatur	e (°C)				
Gas temperature (°C)					
Gas flow rate (standard litres per minute)					
Gas feed type					
Distance between sub-components and tool (mm)					
Heating time (s)					
Removal of heating to sub-component contact time / changed ver time (s)					
Welding force (N)					
Meltdown / collapse / weld	displacement (mm)				
Cooling time (s)					

Compiled by:	Signature:
	Date:
Approved by:	Signature:
	Date:

Joint design

Provide the figure(s) of your joint design here.

STANDARDS 60 COM. Click to view the full POF of 150 235 12:2021

Annex D

(informative)

Template for TJPS: Linear vibration welding

Thermal joining process specification (TJPS): Linear vibration welding

Component name: Customer component/ part number Supplier component/ part number Sub-component A: Sub-component Bc Material type/designation: Material type/designation: Material supplier name Material supplier name Material grade Material grade Material grade Masterbatch reference Masterbatch reference Masterbatch percentage Regrind (%) Moisture content range (%) Regrind (%) Dimensional report number Dimensional report number Process report number Process report number Visual examination acceptance criteria document number Joining parameters Value/tolerance or range Ambient temperature (°C) Frequency (Hz) Amplitude profile IR pre-heat time (s) (if applicable) IR pre-heat time (s) (if applicable) IR pre-heat changeover time (s) (if applicable) Meltdown / collapse / weld displacement (mm) Welding time (s) Hold/cooling time (s)	Joining organization:		TJPS reference number/revision:			
part number JPQR number: Sub-component A: Material type/designation: Material supplier name Material supplier name Material grade Masterbatch reference Masterbatch percentage Regrind (%) Moisture content range (%) Dimensional report number Process report number Process report number Visual examination acceptance criteria document number Visual examination acceptance criteria document temperature (°C) Frequency (Hz) Amplitude (mm) amplitude profile IR pre-heat time (s) (if applicable) IR pre-heat tome (s) (if applicable) Welding force (N) / force profile Meltdown / collapse / weld displacement (mm) Welding time (s)	Component name:		2			
JPQR number:						
Sub-component A: Material type/designation: Material supplier name Material supplier name Material grade Masterbatch reference Masterbatch percentage Regrind (%) Moisture content range (%) Dimensional report number Process report number Process report number Visual examination acceptance criteria document number Joining parameters Ambient temperature (°C) Frequency (Hz) Amplitude (mm) amplitude profile IR pre-heat tome (s) (if applicable) IR pre-heat changeover time (s) (if applicable) Welding force (N) / force profile Meltdown / collapse / weld displacement (mm) Welding time (s)	-		part number			
Material type/designation: Material supplier name Material supplier name Material supplier name Material grade Masterbatch reference Masterbatch percentage Regrind (%) Moisture content range (%) Dimensional report number Process report number Visual examination acceptance criteria document number Visual examination acceptance criteria document number Joining parameters Material type/designation: Material supplier name Material type/designation: Material type/designation: Material type/designation: Material type/designation: Material type/designation: Material type/designation: Material supplier name Material supplied Meltore reference Material supplied Ma	JPQR number:					
Material type/designation: Material supplier name Material supplier name Material supplier name Material grade Masterbatch reference Masterbatch percentage Regrind (%) Moisture content range (%) Dimensional report number Process report number Visual examination acceptance criteria document number Visual examination acceptance criteria document number Joining parameters Material type/designation: Material supplier name Material type/designation: Material type/designation: Material type/designation: Material type/designation: Material type/designation: Material type/designation: Material supplier name Material supplied Meltore reference Material supplied Ma	Γ <u></u>		I	- O'V		
Material supplier name Material grade Material grade Masterbatch reference Masterbatch percentage Regrind (%) Moisture content range (%) Dimensional report number Process report number Process report number Visual examination acceptance criteria document number Joining parameters Ambient temperature (°C) Sub-component temperature (°C) Frequency (Hz) Amplitude (mm) amplitude profile IR pre-heat time (s) (if applicable) IR pre-heat changeover time (s) (if applicable) Welding force (N) / force profile Meltdown / collapse / weld displacement (mm) Welding time (s)			-			
Material grade Masterbatch reference Masterbatch percentage Regrind (%) Moisture content range (%) Dimensional report number Process report number Process report number Visual examination acceptance criteria document number Joining parameters Ambient temperature (°C) Sub-component temperature (°C) Frequency (Hz) Amplitude (mm) Amplitude profile IR pre-heat time (s) (if applicable) IR pre-heat changeover time (s) (if applicable) Welding force (N) / force profile Meltdown / collapse / weld displacement (mm) Welding time (s)	71.	1			I	
Masterbatch reference Masterbatch percentage Regrind (%) Moisture content range (%) Dimensional report number Process report number Process report number Visual examination acceptance criteria document number Joining parameters Ambient temperature (°C) Frequency (Hz) Amplitude (mm) / amplitude profile IR pre-heat tune (s) (if applicable) IR pre-heat tune (s) (if applicable) IR pre-heat changeover time (s) (if applicable) Welding force (N) / force profile Meltdown / collapse / weld displacement (mm) Welding time (s)				, , 		
Masterbatch percentage Regrind (%) Moisture content range (%) Dimensional report number Process report number Visual examination acceptance criteria document number Joining parameters Ambient temperature (°C) Sub-component temperature (°C) Frequency (Hz) Amplitude (mm) amplitude profile IR pre-heat time (s) (if applicable) IR pre-heat power (%) (if applicable) IR pre-heat changeover time (s) (if applicable) Welding force (N) / force profile Meltdown / collapse / weld displacement (mm) Welding time (s)			1			
Regrind (%) Moisture content range (%) Dimensional report number Process report number Visual examination acceptance criteria document number Joining parameters Ambient temperature (°C) Sub-component temperature (°C) Frequency (Hz) Amplitude (mm) / amplitude profile IR pre-heat time (s) (if applicable) IR pre-heat time (s) (if applicable) IR pre-heat changeover time (s) (if applicable) Welding force (N) / force profile Meltdown / collapse / weld displacement (mm) Welding time (s)	Masterbatch reference		Masterbatch	reference		
Moisture content range (%) Dimensional report number Process report number Process report number Visual examination acceptance criteria document number Joining parameters Ambient temperature (°C) Sub-component temperature (°C) Frequency (Hz) Amplitude (mm) / amplitude profile IR pre-heat time (s) (if applicable) IR pre-heat time (s) (if applicable) IR pre-heat changeover time (s) (if applicable) Welding force (N) / force profile Meltdown / collapse / weld displacement (mm) Welding time (s)	Masterbatch percentage		Masterbatch	percentage		
Dimensional report number Process report number Visual examination acceptance criteria document number Value/tolerance or range Ambient temperature (°C) Sub-component temperature (°C) Frequency (Hz) Amplitude (mm) / amplitude profile IR pre-heat time (s) (if applicable) IR pre-heat power (%) (if applicable) IR pre-heat changeover time (s) (if applicable) Welding force (N) / force profile Meltdown / collapse / weld displacement (mm) Welding time (s)	Regrind (%)		Regrind (%)			
Process report number Visual examination acceptance criteria document number Visual examination acceptance criteria document number Visual examination acceptance criteria document number Value/tolerance or range Ambient temperature (°C) Sub-component temperature (°C) Frequency (Hz) Amplitude (mm) / amplitude profile IR pre-heat time (s) (if applicable) IR pre-heat power (%) (if applicable) IR pre-heat changeover time (s) (if applicable) Welding force (N) / force profile Meltdown / collapse / weld displacement (mm) Welding time (s)	Moisture content range (%)		Moisture cor			
Visual examination acceptance criteria document number Visual examination acceptance criteria document number	Dimensional report number	~0~	Dimensional			
Criteria document number Criteria document number	Process report number	at to	Process report number			
Joining parameters Ambient temperature (°C) Sub-component temperature (°C) Frequency (Hz) Amplitude (mm) / amplitude profile IR pre-heat rime (s) (if applicable) IR pre-heat changeover time (s) (if applicable) Welding force (N) / force profile Meltdown / collapse / weld displacement (mm) Welding time (s)		cillo				
Ambient temperature (°C) Sub-component temperature (°C) Frequency (Hz) Amplitude (mm) / amplitude profile IR pre-heat time (s) (if applicable) IR pre-heat power (%) (if applicable) IR pre-heat changeover time (s) (if applicable) Welding force (N) / force profile Meltdown / collapse / weld displacement (mm) Welding time (s)	criteria document number		criteria docu	ıment number		
Ambient temperature (°C) Sub-component temperature (°C) Frequency (Hz) Amplitude (mm) / amplitude profile IR pre-heat time (s) (if applicable) IR pre-heat power (%) (if applicable) IR pre-heat changeover time (s) (if applicable) Welding force (N) / force profile Meltdown / collapse / weld displacement (mm) Welding time (s)	- · ·			I		
Sub-component temperature (°C) Frequency (Hz) Amplitude (mm) / amplitude profile IR pre-heat time (s) (if applicable) IR pre-heat power (%) (if applicable) IR pre-beat changeover time (s) (if applicable) Welding force (N) / force profile Meltdown / collapse / weld displacement (mm) Welding time (s)				Value/tolerance or	range	
Frequency (Hz) Amplitude (mm) / amplitude profile IR pre-heat time (s) (if applicable) IR pre-heat power (%) (if applicable) IR pre-heat changeover time (s) (if applicable) Welding force (N) / force profile Meltdown / collapse / weld displacement (mm) Welding time (s)						
Amplitude (mm) / amplitude profile IR pre-heat time (s) (if applicable) IR pre-heat power (%) (if applicable) IR pre-beat changeover time (s) (if applicable) Welding force (N) / force profile Meltdown / collapse / weld displacement (mm) Welding time (s)						
IR pre-heat time (s) (if applicable) IR pre-heat power (%) (if applicable) IR pre-heat changeover time (s) (if applicable) Welding force (N) / force profile Meltdown / collapse / weld displacement (mm) Welding time (s)						
IR pre-heat power (%) (if applicable) IR pre-heat changeover time (s) (if applicable) Welding force (N) / force profile Meltdown / collapse / weld displacement (mm) Welding time (s)		le				
IR pre-beat changeover time (s) (if applicable) Welding force (N) / force profile Meltdown / collapse / weld displacement (mm) Welding time (s)						
Welding force (N) / force profile Meltdown / collapse / weld displacement (mm) Welding time (s)	IR pre-beat power (%) (if applicable					
Meltdown / collapse / weld displacement (mm) Welding time (s)	IR pre-heat changeover time (s) (if					
Welding time (s)	Welding force (N) / force profile					
	Meltdown / collapse / weld displace					
Hold/cooling time (s)	Welding time (s)					
	Hold/cooling time (s)					

Compiled by:	Signature:
	Date:
Approved by:	Signature:
	Date:

Joint design

STANDARDS 60.COM. Click to view the full PDF of 18023512.2021 Provide the figure(s) of your joint design here.

Amplitude profile diagram (if applicable)

Provide diagram, if applicable.

Force profile diagram (if applicable)

Provide diagram, if applicable.

16

Annex E

(informative)

Template for TJPS: Orbital vibration welding

Joining organization:			TJPS reference number/revision:			
Component name:					~	
Customer component/ part number				Supplier component/part number		
JPQR number:					گې <u>.</u>	
				O'V		
Sub-component A:			Sub-compo			
Material type/designation	n:			e/designation	:	
Material supplier name			Material sur			
Material grade			Material gra			
Masterbatch reference			Masterbatch			
Masterbatch percentage			Masterbatch	n percentage		
Regrind (%)			Regrind (%)			
Moisture content range (%)		Moisture content range (%)				
Dimensional report numb	oer	~0~.	Dimensional report number			
Process report number		4	Process rep	ort number		
Visual examination acceptance criteria document number		Visual examination acceptance criteria document number				
	- Oh					
Joining parameters				Value/tolera	ance or ra	inge
Ambient temperature (°0	\smile					
Sub-component temperature (°C)						
Frequency (Hz)						
Amplitude (mm) / amplitude profile						
Welding force (N) / force profile						
Meltdown/collapse / weld displacement (mm)						
Welding time (s)						
Hold/cooling time (s)						

Compiled by:	Signature:
	Date:
Approved by:	Signature:
	Date:

Joint design

STANDARDS 60.COM. Click to view the full PDF of 18023512.2021 Provide the figure(s) of your joint design here.

Amplitude profile diagram (if applicable)

Provide diagram, if applicable.

Force profile diagram (if applicable)

Provide diagram, if applicable.

18

Annex F

(informative)

Template for TJPS: Spin welding

Thermal joining process specification (TJPS): Spin welding

Joining organization:		TJPS reference number/revision:		
Component name:			2	
Customer component/ part number			nponent/	
JPQR number:			300	
Sub-component A:		Sub-compor		
Material type/designation:			e/designation:	
Material supplier name		Material sup	 	
Material grade		Material gra		
Masterbatch reference		Masterbatch	reference	
Masterbatch percentage		Masterbatch	percentage	
Regrind (%)		Regrind (%)		
Moisture content range (%)	:(0)	Moisture cor	ntent range (%)	
Dimensional report number	207.	Dimensional	report number	
Process report number	at the	Process repo	ort number	
Visual examination acceptance criteria document number Visual exam		nination acceptance ument number		
Machine characteristics				
Machine type (servo drive) inertia):				
			I	
Joining parameters		Value/tolerance or	range	
Ambient temperature (°C)				
Sub-component temperature (°C)				
Head mass (kg) (inertia machines o				
Run-uptime (s) (inertia machines o	only)			
Rotational speed (rpm)				
Down speed (mm/s)				
Welding force (N) / force profile				
Welding time (s)				
Number of rotations (if applicable)	Number of rotations (if applicable)			
Meltdown / collapse / weld displac	cement (mm)			
Hold/cooling time (s)				
Final angular position (°) (if applicable)				

Compiled by:	Signature:
	Date:
Approved by:	Signature:
	Date:

Joint design

STANDARDS 60.COM. Click to view the full PDF of 18023512.2021 Provide the figure(s) of your joint design here.

Force profile diagram (if applicable)

Provide diagram, if applicable.

20

Annex G

(informative)

Template for TJPS: Laser welding

Thermal joining process specification (TJPS): Laser welding				
Joining organization:		TJPS reference number/revision:		
Component name:				
Customer component/			Supplier component/	0.75
part number			part number	
JPQR number:			0	2 ,
Sub-component A:			Sub-component BC	
Material type/designation	:		Material type/designation	1:
Material supplier name			Material supplier name	
Material grade			Material grade	
Masterbatch reference			Masterbatch reference	
Masterbatch percentage			Masterbatch percentage	
Regrind (%)			Regrind (%)	
Moisture content range (%	b)	;(0)	Moisture content range (%	%)
Laser transmission (%)		~0	Laser transmission (%)	
Dimensional report number	er	- CK-	Dimensional report numb	er
Process report number		Clic	Process report number	
Visual examination accept			Visual examination accep	
criteria document number criteria document number				
Joint preparation				
Laser absorber type (if applicable):				
Eduser absorber type inapplicable).				
Machine characteristics				
Machine type (fixed / handheld):				
Wavelength (µm)				
Beam nanipulation system (contour / quasi-simultaneous / simultaneous / mask)				
Beam energy profile/dimensions (e.g. wave guide, Gaussian, flat top or line)				
Focal length of focusing lens (mm) (if applicable)				

Joining parameters	Value/tolerance or range
Ambient temperature (°C)	
Sub-component temperature (°C)	
Laser power (W)	
Peak power (W) (pulse lasers only)	
Pulse energy (J) (pulse lasers only)	
Pulse duration (ms) and repetition rate (Hz) (pulse lasers only)	
Power density (W/mm ²)	o^
Welding / clamping force (N)	001
Scan speed (mm/s) (if applicable)	J. V
Number of passes (if applicable)	25
Weld time (s) (if applicable)	<u></u>
Meltdown / collapse / weld displacement (mm)	.00
Temperature close/loop (°C) (if applicable)	A STATE OF THE STA
Power mapping/zoning (if applicable)	~
Hold/cooling time (s)	00.

Compiled by:	Signature:
	Date:
Approved by:	Signature:
	Date:
Joint design	
Provide the figure(s) of your joint design here.	
Power zone mapping (if applicable)	

Power zone mapping (if applicable) Provide diagram, if applicable.

Annex H

(informative)

Template for TJPS: Hot plate welding

TJPS reference number/revision:

Thermal joining process specification (TJPS): Hot plate welding

Joining organization:

Component name:					Q ²
Customer component/ part number		Supplier compart number		7.3	
JPQR number:				ر ر	
		T		<u> </u>	
Sub-component A:		Sub-compor			
Material type/designation:			e/designatio	n:	
Material supplier name		Material sup	11		
Material grade		Material gra			
Masterbatch reference		Masterbatch	reference		
Masterbatch percentage		Masterbatch	percentage		
Regrind (%)		Regrind (%)			
Moisture content range (%)	;(0)	Moisture coi	ntent range (%)	
Dimensional report number	20,	Dimensional	report numb	oer	
Process report number	at the	Process repo	ort number		
Visual examination acceptan criteria document number	ice Cilio	Visual exam	ination accep ıment numbe	otance er	
	M				
Machine characteristics	-50				
Hot plate / tool surface coating:					
			I		
Joining parameters			Value/toler	ance or	range
Ambient temperature (°C)					
Sub-component temperature	e (°C)				
Plate temperature (°C)					
Meltingforce (N)					
Heating time (s)					
Meltdown / collapse / displa	cement (mm)				
Removal of heating to sub-cover time (s)	omponent contact time	e / changeo-			
Welding force (N)					
Weld collapse/displacement	(mm)				
Hold/cooling time (s)					

Compiled by:	Signature:
	Date:
Approved by:	Signature:
	Date:

STANDARDS GO. COM. Click to view the full POF of 150 235 12:2021 Note a worked example of a TJPS for hot plate welding is given in Annex L.

Joint design

Provide the figure(s) of your joint design here.

24

Annex I

(informative)

Template for TJPS: Heat staking - hot air

Thermal joining process specification (TJPS): Heat staking - hot air					
Joining organization:		TJPS reference number/revision:			
Component name:					2
Customer component/ part number			Supplier component/ part number		
JPQR number:				^တ ္တာ <u>,</u>	
Sub-component A*:			Sub-component BC		
Material type/designation	ı:		Material type/designation:		
Material supplier name			Material supplier name		
Material grade			Material grade		
Masterbatch reference			الان		
Masterbatch percentage					
Regrind (%)			A. A		
Moisture content range (9	6)	;(0)	Moisture content range (%)	
Dimensional report numb	er	.07.	Dimensional report numl	ber	
Process report number		it is	Process report number		
Visual examination accep criteria document numbe		Clio	Visual examination accept criteria document number		

^{*} Sub-component A is the formed part in staking

Joining parameters	Value/tolerance or range
Ambient temperature (°C)	
Sub-component temperature (°C)	
Hot air temperature (°C)	
Air flow (m/s or standard litres per minute)	
Distance of stake pin from end of nozzle (mm)	
Heating time (s)	
Changeover time (s)	
Cold stake tool/platen force (N)	
Cold stake tool contact time (s)	
Final cold tool position / dead stop (mm) (if applicable)	

Compiled by:	Signature:
	Date:
Approved by:	Signature:
	Date:

Joint design

Provide the figure(s) of your joint design here.

STANDARDS 50. COM. Click to view the full PDF of 150 235 N. 2021

Annex J (informative)

Template for TJPS: Heat staking - electrical

Thermal joining proces	s specific	ation (TJPS):	Heat staking - electrical		
Joining organization:		TJPS reference number/revision:			
Component name:					N.
Customer component/ part number			Supplier component/ part number		
JPQR number:				(₁)	
			, and the second	V	
Sub-component A*:			Sub-component BC		
Material type/designatio	n:		Material type/designation	n:	
Material supplier name			Material supplier name		
Material grade			Material grade		
Masterbatch reference			الانه		
Masterbatch percentage					
Regrind (%)			III.		
Moisture content range (%)	:.0	Moisture content range ([%)	
Dimensional report numb	oer	,07,	Dimensional report num	ber	
Process report number		at the	Process report number		
Visual examination accept criteria document number		Click	Visual examination acce criteria document numb		
* Cl	C				

Sub-component A is the formed part in staking

Joining parameters	Value/tolerance or range
Ambient temperature (**)	
Sub-component temperature (°C)	
Heated tool temperature (°C) / temperature profile	
Heating time (s) (if no temperature profile)	
Tool/platen force (N)	
Cooling time (s) (if no temperature profile)	
Release temperature (°C) (if no temperature profile)	
Final cold tool position / dead stop (mm) (if applicable)	

Compiled by:	Signature:
	Date:
Approved by:	Signature:
	Date:

STANDARDS 60.COM. Click to view the full PDF of 18023512.2021 Note a worked example of a TJPS for heat staking – electrical is given in $\underline{\text{Annex } M}$

Joint design

Provide the figure(s) of your joint design here.

Temperature profile (if applicable)

Provide diagram, if applicable.

28

Annex K

(informative)

Template for TJPS: Heat staking - infrared

Thermal joining process specification (TJPS): Heat staking - infrared					
Joining organization:		TJPS reference number/revision:			
Component name:					
Customer component/ part number			Supplier component/ part number		
JPQR number:					
		1	0,1		
		_	-component BC		
		Material type/designation:			
Material supplier name		Material supplier name			
Material grade		Material grade			
Masterbatch reference		EUII III			
Masterbatch percentage		~e`			
Regrind (%)		A.			
Moisture content range (%)	ile)	Moisture content range (%)			
Dimensional report number	*07	Dimensional report number			
Process report number	C. C.	Process report number			
Visual examination acceptance criteria document number	Clic	Visual examination acceptance criteria document number			
* Sub-component A is the formed part in staking					
Joining parameters			Value/tolerance or range		
Ambient temperature (C)					
Sub-component temperature (°C)					
IR power (W)					
Distance of stake pin from heat source (mm)					
Heating time (s)					
Cold stake tool/platen force (N)					
Cold stake tool contact time (s)					
Compiled by:		Signature:			
		Date:			
Approved by: Signature		Signature:			
		Date:			

Joint design

Provide the figure(s) of your joint design here.