

NFPA No.

257

**FIRE TESTS OF
WINDOW
ASSEMBLIES
1975**



Copyright © 1975

NATIONAL FIRE PROTECTION ASSOCIATION

470 Atlantic Avenue, Boston, MA 02210

4M-7-75-FP

Printed in U.S.A.

Official NFPA Definitions

APPROVED: means "acceptable to the authority having jurisdiction."

NOTE: The National Fire Protection Association does not approve, inspect or certify any installations, procedures, equipment or materials nor does it approve or evaluate testing laboratories.

In determining the acceptability of installations or procedures, equipment or materials, the authority having jurisdiction may base acceptance on compliance with NFPA or other appropriate standards. In the absence of such standards, said authority may require evidence of proper installation, procedure or use. The authority having jurisdiction may also refer to the listings or labeling practices of nationally recognized testing laboratories, inspection agencies, or other organizations concerned with product evaluations which are in a position to determine compliance with appropriate standards for the current production of listed items, and the satisfactory performance of such equipment or materials in actual usage.

AUTHORITY HAVING JURISDICTION: The "authority having jurisdiction" is the organization, office, or individual responsible for "approving" equipment, an installation, or a procedure.

NOTE: The phrase "authority having jurisdiction" is used in NFPA standards in a broad manner since jurisdictions and "approval" agencies vary as do their responsibilities. Where public safety is primary, the "authority having jurisdiction" may be a federal, state, local, or other regional department or individual such as a fire chief, fire marshal, chief of a fire prevention bureau, labor department, health department, building official, electrical inspector, or others having statutory authority. For insurance purposes, an insurance inspection department, rating bureau, or other insurance company representative may be the "authority having jurisdiction." In many circumstances the property owner or his delegated agent assumes the role of the "authority having jurisdiction"; at government installations, the commanding officer or departmental official may be the "authority having jurisdiction."

LABELED: Equipment or materials to which has been attached a label, symbol or other identifying mark of a nationally recognized testing laboratory, inspection agency, or other organization concerned with product evaluation, that maintains periodic inspection of production of labeled equipment or materials and by whose labeling is indicated compliance with nationally recognized standards or tests to determine suitable usage in a specified manner.

LISTED: Equipment or materials included in a list published by a nationally recognized testing laboratory, inspection agency, or other organization concerned with product evaluation, that maintains periodic inspection of production of listed equipment or materials and whose listing states either that the equipment or material meets nationally recognized standards or has been tested and found suitable for use in a specified manner.

NOTE: The means for identifying listed equipment may vary for each testing laboratory, inspection agency or other organization concerned with product evaluation, some of which do not recognize equipment as listed unless it is also labeled. The authority having jurisdiction should utilize the system employed by the listing organization to identify a listed product.

SHALL: is intended to indicate requirements.

SHOULD: is intended to indicate recommendations or that which is advised but not required.

Copyright and Republishing Rights

This publication is copyrighted © by the National Fire Protection Association. A royalty-free license is granted to public authorities to print and to publish this publication in whole or in part in laws, ordinances, regulations, administrative orders, or similar documents issued by said public authorities, provided due notice of copyright is contained therein. All other rights in the copyrighted publication, including the right to vend, are retained by the National Fire Protection Association. All others desiring permission to reproduce in any form this publication, in whole or in part, shall consult the National Fire Protection Association.

Statement on NFPA Procedures

This material has been developed under the published procedures of the National Fire Protection Association, which are designed to assure the appointment of technically competent Committees having balanced representation. While these procedures assure the highest degree of care, neither the National Fire Protection Association, its members, nor those participating in its activities accepts any liability resulting from compliance or noncompliance with the provisions given herein, for any restrictions imposed on materials or processes, or for the completeness of the text.

NFPA has no power or authority to police or enforce compliance with the contents of this document and any certification of products stating compliance with requirements of this document is made at the peril of the certifier.

Standard for Fire Tests of Window Assemblies

NFPA 257 — 1975

This edition of NFPA 257 was officially adopted on May 14, 1975 at the Annual Meeting of the Association held in Chicago, IL.

This *Standard* was tentatively adopted by the Association in 1969. It was published and distributed for comment at that time, and since none was received by the Committee, no changes were made in the 1970 edition. The 1975 edition was edited in conformance with the *NFPA Style Manual*, including the use of the new text numbering system, and substantively reconfirmed in May 1975.

Committee on Fire Tests

Jack A. Bono, Chairman,

Underwriters' Laboratories, Inc., 333 Pfingsten Rd., Northbrook, IL 60062

M. S. Abrams, Portland Cement Association
Irwin A. Benjamin, National Bureau of Standards

John A. Blair, E. I. duPont de Nemours & Co., Plastics Dept., Society of the Plastics Industry.

Richard W. Bletzacker, The Ohio State University.

Herbert B. Carlsen, Gypsum Assn.

Robert W. Dougherty, M & M Protection Consultants

Buell B. Dutton (rep. Building Officials & Code Administrators International, Inc.)

Richard G. Gewain, American Iron & Steel Institute

George B. Krumholz, Jr., U.S. Testing Co., Inc. (vote restricted to matters pertaining to textiles)

Gerald E. Lingenfelter, American Insurance Assn.

Gerald L. Maatman, Kemper Insurance Co.
W. F. Maroni, Factory Mutual Research Corp.

E. E. Miller, Factory Insurance Assn.

Henry Omson, Mobile Homes Manufacturers Assn.

Norman S. Pearce, Underwriters' Laboratories of Canada

T. P. Pritsker, The Dallas Laboratories

Dr. A. F. Robertson, Institute of Applied Technology, National Bureau of Standards

John Ed Ryan, National Forest Products Assn.

Louis Segal, Office of State Fire Marshal, Los Angeles, CA (rep. Fire Marshals Assn., of North America)

Louis W. Vaughan, Canadian Sheet Steel Building Institute

Calvin H. Yuill, Southwest Research Institute

Alternates

David E. Brackett, Gypsum Assn. (Alternate to Herbert B. Carlsen)

B. J. Callahan, Factory Mutual Engineering (Alternate to W. F. Maroni)

S. K. Goodwin, Factory Insurance Assn. (Alternate to E. E. Miller)

G. M. Watson, American Insurance Assn. (Alternate to Gerald E. Lingenfelter)

Nonvoting Member

A. J. Bartosic, Rohm & Haas Co.

This list represents the membership at the time the Committee was balloted on the text of this edition. Since that time, changes in the membership may have occurred.

Standard for Fire Tests of Window Assemblies

NFPA 257 — 1975

Chapter 1 General

1-1 Scope.

1-1.1 (a) These methods of fire tests are applicable to window assemblies, including glass block and other light transmitting assemblies, for use in wall openings to retard the passage of fire.

NOTE: It should be noted that assemblies classified in accordance with the provisions of this Standard afford only limited protection from the transmission of heat or against radiation hazard.

(b) Tests made in conformity with these test methods will register performance during the test exposure and develop data to enable regulatory bodies to determine the suitability of window assemblies for use in wall openings where fire protection is required. Such tests shall not be construed as determining suitability of window assemblies for continued use after fire exposure.

Chapter 2 Control of Fire Tests

2-1 Time-Temperature Curve. (*See Figure 2-1.1.*)

2-1.1 The fire exposure of window assemblies shall be controlled to conform to the standard time-temperature curve shown in Figure 2-1.1. The points on the curve that determine its character are:

1000 F (538 C)	at 5 minutes
1300 F (704 C)	at 10 minutes
1399 F (760 C)	at 15 minutes
1462 F (795 C)	at 20 minutes
1510 F (821 C)	at 25 minutes
1550 F (843 C)	at 30 minutes
1584 F (868 C)	at 35 minutes
1613 F (878 C)	at 40 minutes
1638 F (892 C)	at 45 minutes

2-2 Furnace Temperatures.

2-2.1 (a) The temperatures of the test exposure shall be the average temperature obtained from the readings of not less than

nine thermocouples symmetrically disposed and distributed to show the temperature near all parts of the test assembly. The thermocouples shall be protected by sealed porcelain tubes having $\frac{3}{4}$ -inch (19mm) outside diameter and $\frac{1}{8}$ -inch (3mm) wall thickness or, as an alternate in the case of base-metal thermocouples, protected by sealed $\frac{1}{2}$ -inch (13mm) wrought-steel or wrought-iron pipe of standard weight. The exposed length of the thermocouple protection tube in the furnace chamber shall be not less than 12 inches (304.8mm). The junction of the thermocouples shall be 6 inches (152.4mm) from the exposed face of the test assembly or from the masonry in which the assembly is installed, during the entire test exposure.

(b) The temperatures shall be read at intervals not exceeding 5 minutes.

(c) The furnace shall be controlled so that the maximum temperature at individual points shall not exceed 1650 F (900 C) and the area under the time-temperature curve, obtained by averaging the results from the temperature readings, is within 10 percent of the corresponding area under the standard time-temperature curve shown in Figure 2-1.1.

(d) In case the temperature at any point does exceed 1650 F (900 C) the performance of the glass in that area shall be disregarded.




Figure 2-1.1 — Time-Temperature Curve

Chapter 3 Test Assemblies

3-1 Construction and Size.

3-1.1 (a) The design, construction, material, workmanship, and hardware of the test window assembly shall be representative of that for which approval is desired. A record of materials and construction details adequate for identification shall be made.

(b) The area of the test assembly shall be not less than 100 square feet (9.29m^2), with neither dimension less than 9 feet (2.75m). If the conditions of use limit the construction to smaller dimensions, a proportionate reduction may be made in the dimensions of the test assembly for tests qualifying them for such restricted use.

3-2 Mounting.

3-2.1 The test assembly shall be installed in masonry or reinforced concrete frames in the manner in which it is to be used. It shall be mounted so that the latches and fasteners other than hinges shall be on the unexposed side, and the mounting shall not prevent the free and easy operation of all openable components such as ventilators and sash.

Chapter 4 Conduct of Tests

4-1 Time of Testing.

4-1.1 Masonry settings shall be allowed to season at least 7 days, and reinforced concrete settings at least 28 days, before fire tests are made.

4-2 Fire Endurance Test.

4-2.1 (a) The pressure in the furnace chamber shall be maintained as nearly equal to the atmospheric pressure as possible.

(b) The test shall be continued for 45 minutes unless the conditions of acceptance set forth in Chapter 5 are exceeded in a shorter period.

4-3 Hose Stream Test.

4-3.1(a) Immediately following the fire endurance test and within $1\frac{1}{2}$ minutes, the fire exposed side of the test assembly shall be subjected to the impact, erosion, and cooling effects of the hose stream.

(b) The hose stream shall be delivered through a 2½-inch (62mm) hose discharging through a National Standard playpipe of corresponding size equipped with a 1⅞-inch (28mm) discharge tip of the standard-taper smooth-bore pattern without shoulder at the orifice.

(c) The tip of the nozzle shall be located 20 feet (6.1m) from and on a line normal to the center of the test assembly. If impossible to be so located, the nozzle may be on a line deviating not more than 30 degrees from the line normal to the center of the test door. When so located, the distance from the plane of the surface to the test assembly shall be less than 20 feet (6.1m) by an amount equal to 1 foot (0.31m) for each 10 degrees of deviation from the normal.

(d) The hose stream shall be directed around the periphery of the test assembly, starting upward from a lower corner. When the circuit is about 1 foot (0.31m) from the starting point, the hose stream shall be applied in paths about 1 foot (0.31m) apart up and down the assembly across the entire width and then back and forth horizontally across the entire height.

(e) The water pressure at the base of the nozzle shall be 30 pounds per square inch, and the hose stream shall be applied 6/10 second for each square foot of area of the test assembly.

Chapter 5 Conditions of Acceptance

5-1 Window Assemblies. (See Figure 5-1.)

5-1.1 (a) A window assembly shall be considered as meeting the requirements for acceptable performance when it remains in the opening during the fire endurance test and hose stream test within the following limitations:

(b) The window assembly shall not be loosened from its fastenings.

(c) Movement at the perimeter of openable components, from the initial closed position, shall not exceed the thickness of the frame member at any point.

(d) At least 70 percent of the edges of the individual glass lights shall remain in position throughout the hose stream test. The dislodging of small fragments from the central areas of individual lights shall be disregarded.

5-2 Glass Block Assemblies. (*See Figure 5-2.*)

5-2.1 (a) A glass block assembly shall be considered as meeting the requirements for acceptable performance when it remains in the opening during the fire endurance and hose stream tests within the following limitations:

(b) The glass block assembly shall not be loosened from the frame.

(c) At least 70 percent of the glass blocks shall not develop through openings.




Figure 5-1 — Unexposed side of window assembly after fire exposure and hose stream application.




Figure 5-2 — Exposed side of window assembly after fire exposure and hose stream application.