

Synchro, Torque Receiver Transmitter, Type 37TRX4A

FSC 5990

RATIONALE

This Revision consists of a 5 (five) year review, which provides updates to current format and references.

NOTICE

This specification is approved for use by all Departments and Agencies of the Department of Defense. The requirements for acquiring the Synchros described herein shall consist of this specification and the latest issue of SAE AS20708.

SAENORM.COM : Click to view the full PDF of as20708_70a

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2011 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Tel: +1 724-776-4970 (outside USA)
Fax: 724-776-0790
Email: CustomerService@sae.org
<http://www.sae.org>

SAE WEB ADDRESS:

**SAE values your input. To provide feedback
on this Technical Report, please visit
<http://www.sae.org/technical/standards/AS20708/70A>**

TABLE 1. REQUIREMENTS

Requirement	Value	Unit	Tolerance
Frequency	400	Hz	±1%
Primary Voltage	115	volts	±1%
Primary Current	1885	milliamps	maximum
Primary Power	20	watts	maximum
Impedance:			
Zss	3.0 - 4.0	ohms	min.-max.
Impedance Angle:			
Zss	66.0 - 70.0	degrees	min.-max.
Transformation Ratio	0.783	-----	± 2%
Phase Shift (Lead)	1.0	degrees	maximum
Electrical Error	8.0	minutes	min.-max.
Receiver Error	36	minutes	maximum
Null Voltage:			
Total	170	millivolts	maximum
Fundamental	35	millivolts	maximum
Synchronizing Time			
30° ± 2°	1.0	seconds	maximum
Synchronizing Time:			
177° ± 2°	2.0	seconds	maximum
Torque Gradient	0.9	ounce-inches per degree	minimum
Radial Play	0.0008	inches	maximum
End Play	0.0030	inches	±0.0020
Temperature Rise	60.0	degrees (C)	maximum
Variation of Voltage (+10%) and Freq. (-5%)	32.5	watts	maximum

TABLE 2—MILITARY PART NUMBER VARIANT CHARACTERISTICS

Military Part No. ^{1/}	A ± .010	B ± .010	G Maximum	Shaft Style	Terminal End	U + .0000 - .0002
M20708/70-01A	.700	.730	4.030	Splined	Terminal Board	.2405

^{1/} Military part number M20708/70-01A shall be the NATO standard.

^{1/} The suffix letter following the numerical dash number corresponds to the latest modification letter in the type designation.